

INDUSTRIAL COMPONENT DATA

XN-GWBR-CANOPEN 140155 0004520686 EATON ELECTRIC

Gateway for XI/ON I/O system, integrated, bus refresh with

Brand: EATON - MOELLER | Manufacturer Part Number: XN-GWBR-CANOPEN



Manufacturer	EATON - MOELLER
MPN / Reference	XN-GWBR-CANOPEN
Catalog number	0004520686
Category	Fieldbus, decentr. periphery - communication module
Minimum order	1 Pcs
Document ID	EO-69E5C5435C
Generated	2026-08-05

Product Overview

Gateway for XI/ON I/O system, integrated, bus refresh with
XION Gateway; CANopen; With BUS refreshment

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Remote I / O Modules XION
--------------	---

Additional Product Information

Gateway for XI/ON I/O system, integrated, bus refresh with The XI/ON standard I/O system offers the right I/O solution for every application due to its great modularity and large variety of functions. Pluggable modules, hot-swapping of modules, wiring on the basic module screw or tension spring, modules' mechanical coding. The standard gateways support the CANopen bus systems, PROFIBUS-DP deviceNet and Ethernet. Delivery program

Function Gateways XI/ON Function XN-Gateway with integrated supply Short Description supports up to 74 disc-type modules (XN, XNE)

1 x Open Style Connector

Address set with two decimal rotary coding switches

Address range: 1 - 99 (dec.) Field bus connection CANopen® Terminal capacity (field bus/supply voltage) Screw terminals

Service interface PS/2 socket Data transfer rate 1000 Kbit/s

800 Kbit/s

500 Kbit/s

250 Kbit/s

125 kbit/s

50 Kbit/s

20 Kbit/s

10 Kbit/s Instructions Bus refreshing module is already integrated. Information about equipment supplied The delivery package for all gateways includes: 2 x end bracket XN-WEW-32/2-SW, 1 x end plate XN-ABPL Technical data

General Standards EN 61000-6-2

EN 61000-6-4

EN 61131-2 Approvals Approvals CE, cULus Potential isolation Yes, through optocoupler Ambient temperature 0 - +55 °C

Storage [?] -25 - +85 °C Relative humidity 5 - 95 % (indoor), Level RH-2, no condensation (for storage at 45°C) Harmful gases SO₂: 10 (rel. humidity < 75%, no condensation)

H₂S: 1.0 (rel. humidity < 75 %,no condensation) ppm Vibrat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-GWBR-CANOPEN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.