

INDUSTRIAL COMPONENT DATA

BPZ-DT-600/20-P 102440 Y7-102440 EATON ELECTRIC Glass door, for HxW 2060x600mm, Clip-down-handle

Brand: EATON - MOELLER | Manufacturer Part Number: BPZ-DT-600/20-P



Manufacturer	EATON - MOELLER
MPN / Reference	BPZ-DT-600/20-P
Catalog number	Y7-102440
Category	Door/operating panel (switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-0CB8725D82
Generated	2026-08-06

Product Overview

Glass door, for HxW=2060x600mm, Clip-down-handle

BPZ-DT-600/20-P

Service distribution system-Profi Plus (floor standing distribution board, wall-mounting/flush-mounted distribution board)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Enclosures

Additional Product Information

Glass door, for HxW=2060x600mm, Clip-down-handleService distribution system-Profi Plus (floor standing distribution board, wall-mounting/flush-mounted distribution board)

General specificationsProduct nameEaton xEnergy Basic doorPart no.BPZ-DT-600/20-PEAN4015081023288Product Length/Depth45 millimetreProduct height2010 millimetreProduct width615 millimetreProduct weight7.3

kilogramCompliancesRoHS conformProduct TradenamexEnergy BasicProduct TypeAccessoriesProduct Sub TypeDoorDelivery programTypeAdditional equipment for floor-standing service distribution board IVSModelStop doorAccessory/spare part typeDoorsColorLight gray (RAL 7035)

GrayTechnical Data - MechanicalUnit typeModular systemSurface finishingPowder coating

With powder coatingMounting methodFloor standing distribution boardMaterialSteel

Sheet steel/glassDegree of protectionIP30

OtherCover/door colorTransparentCover/door typeRotary leverHousing materialSheet steel/glassSuitable for width600 mmAdditional informationFeaturesVersion as glazed door

EMC-versionFunctionsFloor-standing enclosure

Additional equipmentSpecial featuresCan be used as left door for two-leaf versions
Transparent doors
Single wing door
Mounting from front, fast mounting, hinges on left or right possible
Door opening angle 167°
3-point turn lock with roller lever lock
Transparent panels from 4 mm safety glass (EN 12150-1, DIN 1249)
Left door for two-section design with 1200 mm enclosure widthsUsed withAccessory
Floor-standing enclosure
Accessory con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPZ-DT-600/20-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.