

INDUSTRIAL COMPONENT DATA

GSGB250 EATON ELECTRIC 250AMP 660V AC BS88 SEMI CONDUCTOR FUSE

Brand: EATON - MOELLER | Manufacturer Part Number: GSGB250



Manufacturer	EATON - MOELLER
MPN / Reference	GSGB250
Catalog number	10000
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-B09661CB95
Generated	2026-08-06

Product Overview

250AMP 660V AC BS88 SEMI CONDUCTOR FUSE

Fuse-link, high speed, 250 A, AC 660 V, DC 350 V, BS88, 78 x 107 mm, aR, BS, Ultra fast

Fuse, Fuse-link, high speed, 250 A, AC 660 V, DC 350 V, BS88, 78 x 107 mm, aR, BS, ultra rapid, offset bolted tags,

Protection of semi-conductor devices, BS88-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Bussmann Series High speed fuses**

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse

Catalog Number GSGB250

EAN 5027590502702

Product Length/Depth 143 mm

Product Height 56 mm

Product Width 152 mm

Product Weight 202 g

Compliances CE

Product specifications

Amperage Rating 250 A

Breaking capacity 100 kA

Fuse indicator None
Insulated metal gripping lugs (IMGL) No
Utilization category aR (accompanied semiconductor protection)
Voltage type AC/DC
Rated switching capacity 100 kA
Rated voltage AC 660 V
Rated voltage DC 350 V
Center-to-center distance of connections 81.7 mm
Mounting dimension M10
Current type AC/DC
Class Class aR
Watt losses 46 W
Fuse shape Offset bolted tags
Color None
Construction size Other
Voltage rating 660 V
Type Fuse
Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers
Fuse type GSG
Fuse system (according to IEC 60269) Other
ETIM for GSGB250 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
Other
Type of current (EF000143)
AC/DC
Rated voltage AC (EF007682)
660 V
Rated voltage DC (EF012281)
350 V
Rated current (EF000227)
250 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Breaking capacity (EF005617)
100 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
None
Power loss at rated current (EF012389)
46 W
Mounting holes (EF021553)
M10

Cent...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / GSGB250 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.