

INDUSTRIAL COMPONENT DATA

GSGB30 EATON ELECTRIC Fuse-link, high speed, 30 A, AC 660 V, DC 400 V, BS88, 18 x 80 mm, aR, BS

Brand: EATON - MOELLER | Manufacturer Part Number: GSGB30



Manufacturer	EATON - MOELLER
MPN / Reference	GSGB30
Catalog number	10000
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-1AC14E2753
Generated	2026-08-06

Product Overview

30AMP 660V AC BS88 SEMI CONDUCTOR FUSE

Fuse-link, high speed, 30 A, AC 660 V, DC 400 V, BS88, 17 x 80 mm, aR, BS, Ultra fast

Fuse, Fuse-link, high speed, 30 A, AC 660 V, DC 400 V, BS88, 18 x 80 mm, aR, BS, offset bolted tags, BS88-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number GSGB30 EAN 5027590502719

UPC 051712392273 Product Length/Depth 80 mm Product Height 18 mm Product Width 18 mm Product Weight 33.25 g

Compliances CE Marked Certifications UL Recognized Electrical data

Amperage Rating 30 A Voltage rating 660 V Rated voltage AC 660 V Rated voltage DC 400 V Class Class aR Watt losses

9.6 W Product specifications

Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Fuse indicator None

ETIM for GSGB30 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

660 V

Rated voltage DC (EF012281)

400 V

Rated current (EF000227)

30 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

100 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

9.6 W

Mounting holes (EF021553)

M6

Centre-to-centre distance of connections (EF021151)

61.8 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / GSGB30 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.