

INDUSTRIAL COMPONENT DATA

GSGB630 EATON ELECTRIC Fuse-link, high speed, 630 A, AC 660 V, DC 350 V, BS88, 81 x 143 mm, aR, BS, Ultra fa..

Brand: EATON - MOELLER | Manufacturer Part Number: GSGB630



Manufacturer	EATON - MOELLER
MPN / Reference	GSGB630
Catalog number	10000
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-D92846A9E5
Generated	2026-08-06

Product Overview

630AMP 660V AC BS88 SEMI CONDUCTOR FUSE

Fuse-link, high speed, 630 A, AC 660 V, DC 350 V, BS88, 81 x 143 mm, aR, BS, Ultra fast

Fuse, Fuse-link, high speed, 630 A, AC 660 V, DC 350 V, BS88, 81 x 143 mm, aR, BS, ultra rapid, offset bolted tags (4-barrel), Protection of semi-conductor devices, BS88-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number GSGB630 EAN 5996516024546

Product Length/Depth 143 mm Product Height 80.8 mm Product Width 73.8 mm Product Weight 0.015 g Compliances CE

Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 630 A

Breaking capacity 100 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR

(accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 100 kA Rated voltage AC 660 V

Rated voltage DC 350 V Center-to-center distance of connections 110 mm Mounting dimension M10 Current type AC/DC

Class Class aR Watt losses 117 W Fuse shape Offset 4 barrel bolted tags Color None Construction size Other Voltage

rating 660 V Fuse type GSG Fuse system (according to IEC 60269) Other

ETIM for GSGB630 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

660 V

Rated voltage DC (EF012281)

350 V

Rated current (EF000227)

630 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

100 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

117 W

Mounting holes (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / GSGB630 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.