

INDUSTRIAL COMPONENT DATA

GSGB710 EATON ELECTRIC Fuse-link, high speed, 710 A, AC 660 V, DC 350 V, BS88, 81 x 143 mm, aR, BS, ultra ra..

Brand: EATON - MOELLER | Manufacturer Part Number: GSGB710



Manufacturer	EATON - MOELLER
MPN / Reference	GSGB710
Catalog number	10000
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-4A8F861BDF
Generated	2026-08-06

Product Overview

710AMP 660V AC BS88 SEMI CONDUCTOR FUSE

Fuse-link, high speed, 710 A, AC 660 V, DC 350 V, BS88, 81 x 143 mm, aR, BS, ultra rapid

Fuse, Fuse-link, high speed, 710 A, AC 660 V, DC 350 V, BS88, 81 x 143 mm, aR, BS, ultra rapid, offset bolted tags (4-barrel), Protection of semi-conductor devices, BS88-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Busmann series high speed british standard fuse Catalog Number GSGB710 EAN 5050096007358

Product Length/Depth 73.8 mm Product Height 80.8 mm Product Width 143 mm Product Weight 1147 g Compliances CE

Electrical data

Amperage Rating 710 A Voltage rating 660 V Rated voltage AC 660 V Rated voltage DC 350 V Class Class aR Watt losses 126 W Product specifications

Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Fuse indicator None

ETIM for GSGB710 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

660 V

Rated voltage DC (EF012281)

350 V

Rated current (EF000227)

710 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

100 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

126 W

Mounting holes (EF021553)

M10

Centre-to-centre distance of connections (EF021151)

110 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / GSGB710 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.