

INDUSTRIAL COMPONENT DATA

GSGB800 800AMP 660V AC BS88 SEMI CONDUCTOR FUSE EATON ELECTRIC Fuse-link, high speed, 800 A, AC 660 V, DC 35..

Brand: EATON - MOELLER | Manufacturer Part Number: GSGB800



Manufacturer	EATON - MOELLER
MPN / Reference	GSGB800
Catalog number	800AMP 660V AC BS88 SEMI CONDUCTOR FUSE
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-1AF0B1422A
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 800 A, AC 660 V, DC 350 V, BS88, 81 x 143 mm, aR, BS, Ultra fast

800AMP 660V AC BS88 SEMI CONDUCTOR FUSE

Fuse, Fuse-link, high speed, 800 A, AC 660 V, DC 350 V, BS88, 81 x 143 mm, aR, BS, ultra rapid, offset bolted tags (4-barrel), Protection of semi-conductor devices, BS88-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

Fuse-link, high speed, 800 A, AC 660 V, DC 350 V, BS88, 81 x 143 mm, aR, BS, Ultra fast
Fuse, Fuse-link, high speed, 800 A, AC 660 V, DC 350 V, BS88, 81 x 143 mm, aR, BS, ultra rapid, offset bolted tags (4-barrel), Protection of semi-conductor devices, BS88-4, Breaking Capacity 100 kA

General specifications
Product name Eaton Bussmann series high speed British standard fusePart

no.GSGB800EAN5996516024577Product Length/Depth143 millimetreProduct height80.8 millimetreProduct width73.8

millimetreProduct weight500 gramCompliancesCEProduct TradenameNoneProduct TypeHigh speed British standard
fuseProduct Sub TypeNoneElectrical dataAmperage Rating800 AVoltage rating660 VRated voltage AC660 VRated voltage

DC350 VClassClass aRWatt losses150 WProduct specificationsApplicationSemiconductor, DC Common bus, DC drives,
power converters/rectifiersFuse indicatorNoneTechnical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)Electric engineering, automation, process control

engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (
[BAB264011])Fuse construction type according to IEC 60269OtherType of currentAC/DCRated voltage AC660 VRated
voltage DC350 VRated current800 AUtilization categoryaR (accompanied semiconductor protection)Breaking capacity100
kAColour codeNoneType of fuse status indicatorNonePower loss at rated current150 WMounting holesM10Centre-to-centre
distance of connections110 mm
ETIM for GSGB8...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / GSGB800 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.