

INDUSTRIAL COMPONENT DATA

M22-XGPV 231273 Y7-231273 EATON ELECTRIC Guard-ring, emergency switching off

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XGPV



Manufacturer	EATON - MOELLER
MPN / Reference	M22-XGPV
Catalog number	Y7-231273
Category	Accessories/spare parts for command devices
Minimum order	1 Pcs
Document ID	EO-8120F7AC9C
Generated	2026-08-02

Product Overview

Guard-ring, emergency switching off

M22-XGPV

Eaton Moeller® series M22 Guard-ring, emergency switching off M22-XGPV

Guard-ring, Product range: Accessories, Single unit, Color RAL Value: RAL 1004, Color yellow, Degree of Protection: IP65, Connection to SmartWire-DT: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Guard-ring Catalog Number 231273 Model Code M22-XGPV EAN

4015082312732 Product Length/Depth 79 mm Product Height 50 mm Product Width 65 mm Product Weight 0.046 kg

Compliances CE Marked Certifications UL 508

CSA Std. C22.2 No. 14-05

EN 60947-5

CSA Std. C22.2 No. 94-91

IEC 60947-5

VDE

UL File No.: E29184

CSA

CSA File No.: 012528

CSA Class No.: 3211-03

IEC/EN 60947-5

UL

CSA-C22.2 No. 94-91

CE

UL Category Control No.: NKCR

CSA-C22.2 No. 14-05 Features & Functions

Color Yellow RAL-number 1004 General

Accessory/spare part type Accessory Degree of protection NEMA 13

NEMA 3R

IP65

NEMA 4X

NEMA 12 Product category Accessories Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Communication

Connection to SmartWire-DT No Contacts

Force for positive opening - min 0 N Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole,

current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation,

non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance

of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XGPV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.