

INDUSTRIAL COMPONENT DATA

40071354481 EATON ELECTRIC GuideLed SL 13021.1 CG-S Recessed sym.

Brand: EATON - MOELLER | Manufacturer Part Number: 40071354481



Manufacturer	EATON - MOELLER
MPN / Reference	40071354481
Catalog number	130211
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-3B0AD9EF11
Generated	2026-08-06

Product Overview

GuideLed SL 13021.1 CG-S Recessed sym.

Eaton GuideLed SL 13021.1 CG-S

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Central Battery System
--------------	--

Additional Product Information

General specifications

Product Name Eaton GuideLed SL CG-S Emergency luminaire Catalog Number 40071354481 EAN 4012539342823

Product Length/Depth 80 mm Product Height 40 mm Product Width 80 mm Product Weight 0.26 kg Certifications CE

Product specifications

Battery quality Not applicable Permissible ambient temperature - min -20 °C Permissible ambient temperature - max 40 °C

Protection class II Degree of impact resistance (IK) IK 03 Outdoor use compliance False Explosion protected False

Diameter 80 mm Degree of protection IP41 Mode Maintained / Non-Maintained (M / NM) Lamp type LED not exchangeable

With light source True Lamp power 2 W Monitoring equipment Safety module for monitoring (central fedded system) Power

supply system Central (central battery) Voltage type AC/DC Current Consumption At 220V DC 20 mA Apparent Power At

Mains Operation 8 VA Effective power at mains operation 3.9 W Wiring system Continuous circuit/emergency circuit With

remote switch connection True Reserve-polarity protected True Conductor cross section 2.5 Connection type Plug-in

connection Type of control gear LED operating device current-controlled Type of wiring Suitable for through wiring Nominal

voltage AC - max 240 V Nominal voltage AC - min 220 V Nominal voltage DC 220 V Rated ambient temp acc.

IEC62722-2-1 - Min -20 °C Rated ambient temp acc. IEC62722-2-1 - Max 40 °C Inrush current 1.5 Mounting Method Built-in

Material housing Plastic Color housing White Built-in height/depth 42 mm Built-in Diam...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 40071354481 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.