

INDUSTRIAL COMPONENT DATA

40071353278 EATON ELECTRIC GuideLed SL 13822 1-8h/D CGLine+

Brand: EATON - MOELLER | Manufacturer Part Number: GuideLed SL 13822 1-8h/D CGLine+



Manufacturer	EATON - MOELLER
MPN / Reference	GuideLed SL 13822 1-8h/D CGLine+
Catalog number	40071353278
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-B520268D37
Generated	2026-08-06

Product Overview

GuideLed SL 13822 1-8h/D CGLine+

Eaton GuideLed SL 13822, Safety lighting, Open area, CGLine + technology, LED, Maintained / Non-Maintained operation, IP41, 204lm, 1h/3h/8h selectable duration, Surface

Eaton GuideLed SL 13822, Safety lighting, Surface, Symmetric optics for open area, CGLine + technology, LED, Maintained / Non-Maintained operation, IP41, 204lm, 1h/3h/8h selectable duration

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Central Battery System**

Additional Product Information

General Specification

Product Name Eaton GuideLed SL SC Emergency Luminaire Catalog Number 40071353278 Product Length/Depth 195 mm Product Height 40 mm Product Width 195 mm Product Weight 0.84 kg Certifications CE EAN 4012539344391 Product Specifications

Battery voltage 3.7 V Battery quality Lithium-ion Glow wire test 850 °C Protection class I Outdoor use compliance False Explosion protected False Degree of protection IP41 Fashion Maintained / Non-Maintained (M / NM) Lamp type LED not exchangeable With light source True Lamp holder Other Lamp power 1.6 W Monitoring equipment Safety module for monitoring (central feeded system) Power supply system Peripheral (individual battery) Voltage type AC Power factor .91 Wiring system Continuous circuit/emergency circuit With remote switch connection True Reserve-polarity protected True Conductor cross section 2.5 Connection type Plug-in connection Max. system power 6.7 W Rated life time L70/B50 at 25 °C 50000 hour Rated life time L90/B10 at 25 °C 50000 hour Type of control gear LED operating device current-controlled Type

of wiring Suitable for through wiring Nominal voltage AC - max 240 V Nominal voltage AC - min 220 V Apparent power at mains operation(NM) 6.9 VA Effective power at mains operation (nm) 6.7 W Rated ambient temp acc. IEC62722-2-1 - Min 0 °C Rated ambient temp acc. IEC62722-2-1 - Max 30 °C Nominal operation time - min 1 hour Nominal operation time - max 8 hour Autonomy 1/3/8 hours Mounting Method Ceiling surface mountin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / GuideLed SL 13822 1-8h/D CGLine+ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.