

INDUSTRIAL COMPONENT DATA

GuideLed SL 13851 1-8h/D CGLine+ 40071353280 EATON

ELECTRIC GuideLed SL 13851 1-8h/D CGLine+

Brand: EATON - MOELLER | Manufacturer Part Number: GuideLed SL 13851 1-8h/D CGLine+



Manufacturer	EATON - MOELLER
MPN / Reference	GuideLed SL 13851 1-8h/D CGLine+
Catalog number	40071353280
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-92FE2600B6
Generated	2026-08-06

Product Overview

GuideLed SL 13851 1-8h/D CGLine+

Eaton GuideLed SL 13851, Safety lighting, Recessed, Asymmetric optics for 5lx on safety equipment acc. to EN1838, CGLine + technology, LED, Maintained / Non-Maintained operation, IP41, 204lm, 1h/3h/8h selectable duration

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Central Battery System**

Additional Product Information

ETIM for 40071353280 Luminaires (EC001957)

Feature Name

Feature Value

Mounting method (EF000003)

Built-in

Suitable for labelling type (EF001277)

Other

With pictogram (EF011099)

No

Monitoring equipment (EF008091)

Safety module for monitoring (central feeded system)

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)
Peripheral (individual battery)
Battery technology (EF004351)
Lithium-ions
Lamp type (EF002423)
LED non-replaceable
With light source (EF005905)
Yes
Lamp holder (EF000048)
Other
Number of lighting heads (EF004258)
1
Housing material (EF001596)
Plastic
Housing colour (EF000136)
Grey
Material cover (EF004284)
Plastic opal
Voltage type (EF000187)
AC
Nominal voltage (EF005127)
220 V
Type of control gear (EF000381)
LED driver constant current
Light distributor (EF012170)
Focal lens
Rated life time L70/B50 at 25 °C (EF011870)
50000 h
Degree of protection (IP) (EF005474)
IP41
Impact strength (EF004293)
IK03
Protection class according to IEC 61140 (EF000004)
II
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)
No
Rated ambient temperature according to IEC 62722-2-1 (EF012090)
0 °C
Max. system power (EF009347)
6.7 W
Rated luminous flux according to IEC 62722-2-1 (EF009349)
115 lm
Colour temperature (EF009346)
6500 K
Power factor (EF025740)
0.91
Nominal operation time (EF012518)

1 h
Width (EF000008)
100 mm
Height/depth (EF001456)
100 mm
Length (EF001438)
354 mm
Built-in width (EF000846)
100 mm
Built-in height/...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / GuideLed SL 13851 1-8h/D CGLine+ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.