

INDUSTRIAL COMPONENT DATA

GVK-10/3P-3TE EP-501073 Y7-501073 EATON ELECTRIC
GVK-10/3P-3TE

Brand: EATON - MOELLER | Manufacturer Part Number: GVK-10/3P-3TE

	Manufacturer	EATON - MOELLER
	MPN / Reference	GVK-10/3P-3TE
	Catalog number	Y7-501073
	Category	Phase busbar
	Minimum order	1 Pcs
	Document ID	EO-9B19868E1B
	Generated	2026-08-05

Product Overview

GVK-10/3P-3TE

GVK-10/3P-3TE, GVK busbar fork, 3-phase, L1 - L2 - L3, shortenable version, end caps not included, 1 meter, 10 mm² Busbar for miniature circuit-breaker, residual-current circuit-breakers, combined residual-current/power circuit-breaker, can be cut to length, RAL 7035 color, halogen free (DIN EN 60754-1), fire class according to V2, testing by VDE (DIN EN 61439-1:2021-10, DIN EN 61439-6:2013-06) PC-ABS isolation material and PP touch protection material, disruptive strength of 36 kV/mm and overvoltage category III

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Moeller series busbar Catalog Number EP-501073 Model Code GVK-10/3P-3TE EAN 9010653035176 Product Length/Depth 1016 mm Product Height 28.5 mm Product Width 15 mm Product Weight 0.428 kg Certifications CE Product specifications Features Insulated Can be cut to size Electric connection type Fork Cross section 10 mm² Number of modular spacings 57 Number of phases 3 Pitch dimensions 17.8 mm Rated operating voltage (Ue) - max 415 V Rated surge voltage 4 KV Rated uninterrupted current (Iu) 63 A Rated short-time withstand current (Icw) 0 kA Number of poles Three-pole Color Grey Rated conditional short-circuit current (Iq) 25 kA Suitable for 19 devices ETIM for EP-501073 Low-voltage industrial controls and switchgear (EC000215)

Feature Name	
Feature Value	
Number of phases (EF000351)	
3	
Number of poles (EF001391)	
3	
Suitable for number of devices (EF007241)	
19	
Module width (EF007504)	
17.8 mm	
Cross section (EF000649)	
10 mm ²	
Length (EF001438)	
1016 mm	
Can be cut to size (EF015250)	
Yes	
Width in number of modular spacings (EF002950)	
57	
Rated permanent current I _u (EF001389)	
63 A	
Type of electric connection (EF003961)	
Fork	
Insulated (EF000019)	
Yes	
Rated surge voltage (EF002993)	
4 kV	
Conditioned rated short-circuit current I _q (EF001444)	
25 kA	
Max. rated operation voltage U _e (EF007357)	
415 V	
Rated short-time withstand current I _{cw} (EF007050)	
0 kA	
Suitable for devices with N-conductor (EF007218)	
No	
Suitable for devices with auxiliary switch (EF007217)	
No	
C...	

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / GVK-10/3P-3TE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.