

INDUSTRIAL COMPONENT DATA

GVK-16/3P+N-4TE EP-501074 Y7-501074 EATON ELECTRIC GVK-16/3P+N-4TE

Brand: EATON - MOELLER | Manufacturer Part Number: GVK-16/3P+N-4TE

	Manufacturer	EATON - MOELLER
	MPN / Reference	GVK-16/3P+N-4TE
	Catalog number	Y7-501074
	Category	Phase busbar
	Minimum order	1 Pcs
	Document ID	EO-5988E02094
	Generated	2026-08-05

Product Overview

GVK-16/3P+N-4TE

GVK-16/3P+N-4TE, GVK busbar fork, 3-phase+N, L1 - L2 - L3 - N, shortenable version, end caps not included, 1 meter, 16 mm²

Busbar for miniature circuit-breaker, residual-current circuit-breakers, combined residual-current/power circuit-breaker, can be cut to length, RAL 7035 color, halogen free (DIN EN 60754-1), fire class according to V2, testing by VDE (DIN EN 61439-1:2021-10 DIN EN 61439-6:2013-06) PC-ABS isolation material and PP touch protection material, disruptive strength of 36 kV/mm and overvoltage category III

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Modular Switchgear - Others and Accessories**

Additional Product Information

General specifications

Product Name Eaton Moeller series busbar Catalog Number EP-501074 Model Code GVK-16/3P+N-4TE EAN 9010653035183 Product Length/Depth 1016 mm Product Height 31.5 mm Product Width 21 mm Product Weight 0.789 kg Certifications CE Product specifications

Features Insulated

Can be cut to size Electric connection type Fork Cross section 16 mm² Number of modular spacings 56 Number of phases 3 Pitch dimensions 17.8 mm Rated operating voltage (Ue) - max 415 V Rated surge voltage 4 KV Rated uninterrupted current (Iu) 80 A Rated short-time withstand current (Icw) 0 kA Number of poles Four-pole Color Grey Rated conditional short-circuit current (Iq) 25 kA Suitable for Devices with N-busbar

14 devices

ETIM for EP-501074 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

3

Number of poles (EF001391)

4

Suitable for number of devices (EF007241)

14

Module width (EF007504)

17.8 mm

Cross section (EF000649)

16 mm²

Length (EF001438)

1016 mm

Can be cut to size (EF015250)

Yes

Width in number of modular spacings (EF002950)

56

Rated permanent current I_u (EF001389)

80 A

Type of electric connection (EF003961)

Fork

Insulated (EF000019)

Yes

Rated surge voltage (EF002993)

4 kV

Conditioned rated short-circuit current I_q (EF001444)

25 kA

Max. rated operation voltage U_e (EF007357)

415 V

Rated short-time withstand current I_{cw} (EF007050)

0 kA

Suitable for devices with N-conductor (EF007218)

Yes

Suitable for devices with auxiliar...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / GVK-16/3P+N-4TE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.