

INDUSTRIAL COMPONENT DATA

SVB-SW-P1/M 172842 Y7-172842 EATON ELECTRIC Handle, black, lockable, for metal shaft, for padlock, for P1

Brand: EATON - MOELLER | Manufacturer Part Number: SVB-SW-P1/M



Manufacturer	EATON - MOELLER
MPN / Reference	SVB-SW-P1/M
Catalog number	Y7-172842
Category	Handle for power circuit breaker
Minimum order	1 Pcs
Document ID	EO-0644F770CF
Generated	2026-08-04

Product Overview

Handle, black, lockable, for metal shaft, for padlock, for P1

SVB-SW-P1/M

Eaton Moeller® series SVB Handle, black, lockable, for metal shaft, for padlock, for P1

Handle, Basic function: Assembly kits, Function: main switch assembly kits, only for main switch, With padlocking feature, for interlocking the 0 position, Lockable with a maximum of 3 padlocks, For use with: P1.../M..., Black, Type With black rotary handle and black locking ring, Emergency switching off/emergency stop: without emergency switching off/emergency stop function, Switching angle: 90 °

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series SVB Accessory Handle Catalog Number 172842 Model Code SVB-SW-P1/M EAN 4015081694242 Product Length/Depth 80 mm Product Height 65 mm Product Width 65 mm Product Weight 0.09 kg

Compliances CE Features & Functions

Color Black Features Lockable Fitted with: Padlocking feature Locking facility Lockable with a maximum of 3 padlocks

Locking mechanism Lockable in the 0 (Off) position (interlock) General

Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Degree of protection NEMA Other

Suitable for Only for main switch

Switch disconnecter Switching angle 90 ° Type Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switch...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SVB-SW-P1/M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.