

INDUSTRIAL COMPONENT DATA

SVB-P3/M 172841 Y7-172841 EATON ELECTRIC Handle, red/yellow, lockable, for metal shaft, for padlock, for P3

Brand: EATON - MOELLER | Manufacturer Part Number: SVB-P3/M



Manufacturer	EATON - MOELLER
MPN / Reference	SVB-P3/M
Catalog number	Y7-172841
Category	Handle for power circuit breaker
Minimum order	1 Pcs
Document ID	EO-E8402AC81D
Generated	2026-08-04

Product Overview

Handle, red/yellow, lockable, for metal shaft, for padlock, for P3

SVB-P3/M

Eaton Moeller® series SVB Handle, red/yellow, lockable, for metal shaft, for padlock, for P3

Handle, Basic function: Assembly kits, Function: main switch assembly kits, only for main switch, With padlocking feature, for interlocking the 0 position, Lockable with a maximum of 3 padlocks, For use with: P3.../M..., red/yellow, Type With red rotary handle and yellow locking ring, Emergency switching off/emergency stop: as emergency switching off/emergency stop function, Switching angle: 90 °

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series SVB Accessory Handle Catalog Number 172841 Model Code SVB-P3/M EAN 4015081694235 Product Length/Depth 88 mm Product Height 88 mm Product Width 88 mm Product Weight 0.13 kg

Compliances CE Features & Functions

Color Red Features Lockable Fitted with: Padlocking feature Functions Emergency stop function

Emergency switching off function Locking facility Lockable with a maximum of 3 padlocks Locking mechanism Lockable in the 0 (Off) position (interlock) General

Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Degree of protection NEMA Other Suitable for Switch disconnector

Emergency stop

Only for main switch Switching angle 90 ° Type Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Meets the product st...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SVB-P3/M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.