

INDUSTRIAL COMPONENT DATA

LSR-S11-1-I/TKG 106847 EATON ELECTRIC Hasp-operated safety switch, 1N/O+1N/C, insulated material

Brand: EATON - MOELLER | Manufacturer Part Number: LSR-S11-1-I/TKG



Manufacturer	EATON - MOELLER
MPN / Reference	LSR-S11-1-I/TKG
Catalog number	106847
Category	End switch
Minimum order	1 Pcs
Document ID	EO-4810155F9F
Generated	2026-08-06

Product Overview

Hasp-operated safety switch, 1N/O+1N/C, insulated material

Safety position switch Plastic 1 NO + 1 NC For lid

Hasp-operated safety switch, LSR, Hasp-operated safety switch, Complete unit, 1 N/O, 1 NC, Insulated material, Screw terminal, -25 - +70 °C

Hasp-operated safety switch, Basic function: Position switches, Safety position switches, Part group reference: LSR,

Product range: Hasp-operated safety switch, Degree of Protection: IP65, Features: Complete unit, Ambient temperature:

-25 - +70 °C, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Housing: Insulated material, Connection type: Screw terminal, Standards: IEC/EN 60947

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Position Switches
--------------	-------------------------------------

Additional Product Information

Hasp-operated safety switch, LSR, Hasp-operated safety switch, Complete unit, 1 N/O, 1 NC, Insulated material, Screw terminal, -25 - +70 °C Hasp-operated safety switch, Basic function: Position switches, Safety position switches, Part group reference: LSR, Product range: Hasp-operated safety switch, Degree of Protection: IP65, Features: Complete unit, Ambient temperature: -25 - +70 °C, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Housing: Insulated material, Connection type: Screw terminal, Standards: IEC/EN 60947 Delivery program
Basic function Position switches

Safety position switches Part group reference LSR Product range Hasp-operated safety switch Degree of Protection IP65
Features Complete unit Ambient temperature -25 - +70 °C Approval Contacts N/O = Normally open 1 N/O N/C = Normally closed 1 NC Notes = safety function, by positive opening to IEC/EN 60947-5-1 Contact sequence Contact travel? = Contact closed? = Contact open Housing Insulated material Connection type Screw terminal Technical data
General Standards IEC/EN 60947 Climatic proofing Damp heat, constant, to IEC 60068-2-78; damp heat, cyclical, to IEC 60068-2-30 Ambient temperature -25 - +70 °C Mounting position As required Degree of Protection IP65 Terminal capacitiesSolid 1 x (0.75 - 2.5)
2 x (0.75 - 1.5) mm² Terminal capacitiesFlexible with ferrule 1 x (0.5 - 1.5)
2 x (0.5 - 1.5) mm² Repetition accuracy 0.02 m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LSR-S11-1-I/TKG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.