

INDUSTRIAL COMPONENT DATA

HF5-500/1A 741E0029 Y7-135422 EATON ELECTRIC HF5 Current Transformer, 500A/1A

Brand: EATON - MOELLER | Manufacturer Part Number: HF5-500/1A



Manufacturer	EATON - MOELLER
MPN / Reference	HF5-500/1A
Catalog number	Y7-135422
Category	Current transformer
Minimum order	1 Pcs
Document ID	EO-CC8337AAB4
Generated	2026-08-05

Product Overview

HF5 Current Transformer, 500A/1A

Current transformer HF5, 500A/1A

Current transformer HF5, Class 0.5, single phase, 500A/1A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

Current transformer HF5, 500A/1ACurrent transformer HF5, Class 0.5, single phase, 500A/1A

General specificationsProduct nameEaton Distribution partsPart no.HF5-500/1AEAN5703498701620Product

Length/Depth83 millimetreProduct height52 millimetreProduct width105 millimetreProduct weight0.645

kilogramCompliancesRoHS conformProduct TradenameNoneProduct TypeDistribution partsProduct Sub TypeNonePublic

ConsumptionYesProduct Family DescriptionES-PMCC-PDC-Eaton Distribution partsGlobally MarketableYesProduct

Specification DetailsAccuracy class (ratio)3ModelThrough-feed current converterNominal current500 ANumber of inputs

(primary)1Opening diameter39 mmOpening height - max13 mmOpening height - min13 mmOpening width - max61

mmOpening width - min61 mmOver current limiting factorFS 5Secondary connectionScrew connectionSecondary current

input1 ASecondary rated apparent power15 V·ATechnical data ETIM 9.0

Low-voltage industrial components (EG000017) / Current transformer (EC002048)Electric engineering, automation, process control engineering / Signal processing / Transformer / Current transformer (ecl@ss13-27-21-09-02

[AAB626019])ModelThrough-feed current converterRated primary current500 ARated secondary current1 ARated

secondary apparent power15 VAPower consumptionWAccuracy class3Overcurrent limiting factorFS 5CalibratedNoWith

shock protectionNoHeight opening13 - 13 mmWidth opening61 - 61 mmOpening diameter39 mmSnap mountingYesWith
copper railNoSecondary connectionScrew connectionNumber o...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / HF5-500/1A with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.