

INDUSTRIAL COMPONENT DATA

HF5-750/5A 741E0034 Y7-135427 EATON ELECTRIC HF5 Current Transformer, 750A/5A

Brand: EATON - MOELLER | Manufacturer Part Number: HF5-750/5A



Manufacturer	EATON - MOELLER
MPN / Reference	HF5-750/5A
Catalog number	Y7-135427
Category	Current transformer
Minimum order	1 Pcs
Document ID	EO-CBB1268071
Generated	2026-08-02

Product Overview

HF5 Current Transformer, 750A/5A
Current transformer HF5, 750A/5A
Current transformer HF5, Class 0.5, single phase, 750A/5A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

Current transformer HF5, 750A/5A
Current transformer HF5, Class 0.5, single phase, 750A/5A
General specifications
Product name Eaton Distribution parts
Part no. HF5-750/5A
EAN 5703498701675
Product Length/Depth 83 millimetre
Product height 52 millimetre
Product width 105 millimetre
Product weight 0.605 kilogram
Compliance RoHS conform
Product Tradename None
Product Type Distribution parts
Product Sub Type None
Public Consumption Yes
Product Family Description ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable Yes
Product Specification Details
Accuracy class (ratio) 3
Model Through-feed current converter
Nominal current 750 A
Number of inputs (primary) 1
Opening diameter 39 mm
Opening height - max 13 mm
Opening height - min 13 mm
Opening width - max 61 mm
Opening width - min 61 mm
Over current limiting factor FS 5
Secondary connection Screw connection
Secondary current input 5 A
Secondary rated apparent power 15 V·A
Technical data ETIM 9.0
Low-voltage industrial components (EG000017) / Current transformer (EC002048)
Electric engineering, automation, process control engineering / Signal processing / Transformer / Current transformer (ecl@ss13-27-21-09-02 [AAB626019])
Model Through-feed current converter
Rated primary current 750 A
Rated secondary current 5 A
Rated secondary apparent power 15 VA
Power consumption W
Accuracy class 3
Overcurrent limiting factor FS 5
Calibrated No
With

shock protectionNoHeight opening13 - 13 mmWidth opening61 - 61 mmOpening diameter39 mmSnap mountingYesWith
copper railNoSecondary connectionScrew connectionNumber o...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / HF5-750/5A with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.