

## INDUSTRIAL COMPONENT DATA

# High Speed British Standard GSGB125 EATON ELECTRIC Fuse-link, high speed, 125 A, AC 660 V, DC 400 V, BS88, 3..

Brand: EATON - MOELLER | Manufacturer Part Number: High Speed - British Standard



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | EATON - MOELLER               |
| MPN / Reference | High Speed - British Standard |
| Catalog number  | GSGB125                       |
| Category        | HRC fuse                      |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-69DFAA572C                 |
| Generated       | 2026-08-06                    |

## Product Overview

Fuse-link, high speed, 125 A, AC 660 V, DC 400 V, BS88, 36 x 95 mm, aR, BS, Ultra fast  
125AMP 660V AC BS88 SEMI CONDUCTOR FUSE

Fuse, Fuse-link, high speed, 125 A, AC 660 V, DC 400 V, BS88, 36 x 95 mm, aR, BS, ultra rapid, offset bolted tags (dual barrel), Protection of semi-conductor devices, BS88-4, Breaking Capacity 100 kA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

## Additional Product Information

Fuse-link, high speed, 125 A, AC 660 V, DC 400 V, BS88, 36 x 95 mm, aR, BS, Ultra fast Fuse, Fuse-link, high speed, 125 A, AC 660 V, DC 400 V, BS88, 36 x 95 mm, aR, BS, ultra rapid, offset bolted tags (dual barrel), Protection of semi-conductor devices, BS88-4, Breaking Capacity 100 kA Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I] 125 A Rated voltage AC 660 V DC 400 V Construction size BS88 Size 36 x 95 mm Utilization category aR Breaking Capacity 100 kA usable for size/applications Protection of semi-conductor devices Release characteristic [class] ultra rapid Standard/Approval BS Shape offset bolted tags (dual barrel) Standards/Regulations BS88-4 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ([email protected]) [AFZ800015]) Construction size Other Rated current 125 A Rated voltage 660 V Voltage type AC/DC Rated switching capacity 100 kA Utilization category aR (accompanied semiconductor protection) Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No

ETIM for GSGB125 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

Other

Rated current (EF000227)

25 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semicondu...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / High Speed - British Standard with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.