

INDUSTRIAL COMPONENT DATA

FUSE 160A 750V 1*EK/155 GDC DC 170E3587 EATON

ELECTRIC Fuse-link, high speed, 160 A, DC 750 V, compact size ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 160A 750V 1*EK/155 GDC DC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 160A 750V 1*EK/155 GDC DC
Catalog number	170E3587
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-2DF7ABDA22
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 160 A, DC 750 V, compact size 1, 43 x 60 x 212 mm, gR, IEC, with indicator, 155 mm centres
FUSE 160A 750V 1*EK/155 GDC DC

Eaton Bussmann series high speed traction fuse, 160 A, 750 V, gR (general purpose semiconductor protection), compact size 1, slotted center bolted tags

Fuse, Fuse-link, high speed, 160 A, DC 750 V, compact size 1, 43 x 60 x 212 mm, gR, IEC, with indicator, square body with centre-bolted tags (slotted), french style, indicator style K for microswitch, traction, IEC 60269-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed traction fuse Catalog Number 170E3587 EAN 5996516006412 UPC 051712209298 Product Length/Depth 129 mm Product Height 61 mm Product Width 43 mm Product Weight 942 g

Compliances RoHS Compliant

IEC Electrical data

Amperage Rating 160 A Voltage rating 750 V Voltage type DC Pre arc (I2T) 7700 Watt losses 26 W Breaking capacity 100 kA Class Class gR Product specification

Fuse size 1*

ETIM for 170E3587 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

DC

Rated voltage DC (EF012281)

750 V

Rated current (EF000227)

160 A

Utilization category according to IEC 60269 (EF002572)

gR (general purpose semiconductor protection)

Breaking capacity (EF005617)

100 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

Other

Power loss at rated current (EF012389)

26 W

Mounting holes (EF021553)

M8

Centre-to-centre distance of connections (EF021151)

156 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 160A 750V 1*EK/155 GDC DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.