

INDUSTRIAL COMPONENT DATA

FUSE 100A 4000V 1*SKN/394ADC DC 170E3933 EATON

ELECTRIC Fuse-link, high speed, 100 A, DC 4000 V, compact siz..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 100A 4000V 1*SKN/394ADC DC

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 100A 4000V 1*SKN/394ADC DC
Catalog number	170E3933
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-5DB67952FA
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 100 A, DC 4000 V, compact size 1, 57 x 70 x 414 mm, aR, IEC, with indicator

FUSE 100A 4000V 1*SKN/394ADC DC

Fuse, Fuse-link, high speed, 100 A, DC 4000 V, compact size 1, 57 x 70 x 414 mm, aR, IEC, with indicator, square body with offset bolted tags, indicator style K for microswitch, traction, Breaking Capacity 60 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Busmann series high speed traction fuse Catalog Number 170E3933 EAN 5996516006566 UPC 051712209519 Product Length/Depth 414 mm Product Height 70 mm Product Width 57 mm Product Weight 1551 g

Compliances EAC Certifications IEC Electrical data

Amperage Rating 100 A Voltage rating 4000 V Voltage type DC Watt losses 114 W Breaking capacity 60 A Class Class aR Product specification

Fuse size 1* Fitted with: Single slot tags

ETIM for 170E3933 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
Other
Type of current (EF000143)
DC
Rated voltage DC (EF012281)
4000 V
Rated current (EF000227)
100 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Breaking capacity (EF005617)
0.06 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
Top fuse status indicator
Power loss at rated current (EF012389)
114 W
Mounting holes (EF021553)
M8
Centre-to-centre distance of connections (EF021151)
395 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 100A 4000V 1*SKN/394ADC DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.