

INDUSTRIAL COMPONENT DATA

FUSE 32A 2000V 1*SKN/246 DC AR 170E3939 EATON

ELECTRIC Fuse-link, high speed, 32 A, DC 2000 V, compact size ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 32A 2000V 1*SKN/246 DC AR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 32A 2000V 1*SKN/246 DC AR
Catalog number	170E3939
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-AC3E399001
Generated	2026-08-05

Product Overview

Fuse-link, high speed, 32 A, DC 2000 V, compact size 1, 57 x 70 x 266 mm, aR, IEC, with indicator

FUSE 32A 2000V 1*SKN/246 DC AR

Fuse, Fuse-link, high speed, 32 A, DC 2000 V, compact size 1, 57 x 70 x 266 mm, aR, IEC, with indicator, square body with offset bolted tags, indicator style K for microswitch, traction, Breaking Capacity 40 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Busmann series high speed traction fuse Catalog Number 170E3939 EAN 5996516006580 Product Length/Depth 416 mm Product Height 57 mm Product Width 73 mm Product Weight 0.9 kg Compliances EAC Certifications IEC Electrical data

Amperage Rating 32 A Voltage rating 2000 V Voltage type DC Watt losses 20 W Breaking capacity 40 kA Class Class aR ETIM for 170E3939 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

DC

Rated voltage DC (EF012281)

2000 V

Rated current (EF000227)

32 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

40 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

Top fuse status indicator

Power loss at rated current (EF012389)

20 W

Mounting holes (EF021553)

M8

Centre-to-centre distance of connections (EF021151)

247 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 32A 2000V 1*SKN/246 DC AR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.