

INDUSTRIAL COMPONENT DATA

FUSE 25A 6000V 1BKN/300 AR 170E5200 EATON ELECTRIC

Fuse-link, high speed, 25 A, AC 6 kV, size 1, 65 x 70 x 3..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 25A 6000V 1BKN/300 AR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 25A 6000V 1BKN/300 AR
Catalog number	170E5200
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-6248B69377
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 25 A, AC 6 kV, size 1, 65 x 70 x 300 mm, aR, IEC, with indicator

FUSE 25A 6000V 1BKN/300 AR

Fuse, Fuse-link, high speed, 25 A, AC 6 kV, size 1, 65 x 70 x 300 mm, aR, IEC, with indicator, square body with flush end contacts, indicator style K for microswitch, IEC 60269-4, Breaking Capacity 50 kA, Optional accessories microswitch 170H0069

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Busmann series high speed square body fuse Catalog Number 170E5200 EAN 5996516006795
UPC 051712799874 Product Length/Depth 295 mm Product Height 70 mm Product Width 65 mm Product Weight 0.001 g
Compliances EAC Certifications IEC Electrical data
Amperage Rating 25 A Voltage rating 6000 V Watt losses 15 W Breaking capacity 50 kA Class Class aR Product specification

Fuse size 1

ETIM for 170E5200 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

IEC 60269-4 flush end connections type A

Fuse construction type according to IEC 60269 (EF015865)

1

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

6000 V

Rated current (EF000227)

25 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

50 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

Top fuse status indicator

Power loss at rated current (EF012389)

15 W

Mounting holes (EF021553)

M8

Centre-to-centre distance of connections (EF021151)

295 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 25A 6000V 1BKN/300 AR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.