

INDUSTRIAL COMPONENT DATA

FUSE 400A 750V 2EK/170 GR DC 170E8347 EATON ELECTRIC

Fuse-link, high speed, 400 A, DC 750 V, size 2, gR, IEC..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 400A 750V 2EK/170 GR DC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 400A 750V 2EK/170 GR DC
Catalog number	170E8347
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-7DC10FEA78
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 400 A, DC 750 V, size 2, gR, IEC, with indicator

FUSE 400A 750V 2EK/170 GR DC

Eaton Bussmann series high speed square body fuse, 400A, 100 kAIC, Other, Fuse, Class gR

Fuse, Fuse-link, high speed, 400 A, DC 750 V, size 2, gR, IEC, with indicator, square body with centre-bolted tags (slotted), french style, indicator style K for microswitch, traction, IEC 60269-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed traction fuse Catalog Number 170E8347 EAN 5996516007198 UPC 051712806657 Product Length/Depth 130 mm Product Height 77 mm Product Width 59 mm Product Weight 1300 g

Compliances RoHS Compliant

IEC Electrical data

Amperage Rating 400 A Voltage rating 750 V Voltage type DC Pre arc (I2T) 55000 Watt losses 73 W Breaking capacity 100 kA Class Class gR Product specification

Fuse size 2

ETIM for 170E8347 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
2
Type of current (EF000143)
DC
Rated voltage DC (EF012281)
750 V
Rated current (EF000227)
400 A
Utilization category according to IEC 60269 (EF002572)
gR (general purpose semiconductor protection)
Breaking capacity (EF005617)
100 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
Other
Power loss at rated current (EF012389)
73 W
Mounting holes (EF021553)
Other
Centre-to-centre distance of connections (EF021151)
170 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 400A 750V 2EK/170 GR DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.