

INDUSTRIAL COMPONENT DATA

FUSE 315A 900V 2KW/110 AR 170E8749 EATON ELECTRIC

Fuse-link, high speed, 315 A, AC 900 V, DIN 2, aR, DIN, wi..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 315A 900V 2KW/110 AR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 315A 900V 2KW/110 AR
Catalog number	170E8749
Category	HRC fuse
Minimum order	3 Pcs
Document ID	EO-198D5FCF9A
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 315 A, AC 900 V, DIN 2, aR, DIN, with indicator

FUSE 315A 900V 2KW/110 AR

FUSE 315A 900V 2KW/110 AR - Fuse-link, high speed, 315 A, AC 900 V, 50 kA, DIN 2, aR, DIN, type K indicator

Fuse, Fuse-link, high speed, 315 A, AC 900 V, DIN 2, aR, DIN, with indicator, square body with centre-bolted tags (slotted), indicator style K for microswitch, DIN 43653, Breaking Capacity 50 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 315 A, AC 900 V, 50 kA, DIN 2, aR, DIN, type K indicator
Fuse, Fuse-link, high speed, 315 A, AC 900 V, DIN 2, aR, DIN, with indicator, square body with centre-bolted tags (slotted), indicator style K for microswitch, DIN 43653, Breaking Capacity 50 kA
Delivery program

Product rangeFuseBasic functionFuse-linkField of applicationhigh speedRated current [I]_N315 ARated voltageAC 900 VConstruction sizeDIN 2Utilization categoryaRStatus indicator type K indicatorBreaking Capacity50

kAStandard/ApprovalDINShapesquare body with centre-bolted tags (slotted)Standards/RegulationsDIN 43653Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015])Construction sizeOtherRated current315 ARated voltage900 VVoltage typeACRated switching capacitykAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorOtherInsulated metal

gripping lugs (IMGL)No

ETIM for 170E8749 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

2

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

900 V

Rated current (EF000227)

315 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 315A 900V 2KW/110 AR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.