

INDUSTRIAL COMPONENT DATA

FUSE 200A 4000V 2SKN/394 DC 170E8883 EATON ELECTRIC

Fuse-link, high speed, 200 A, DC 4000 V, size 2, 75 x 86..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 200A 4000V 2SKN/394 DC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 200A 4000V 2SKN/394 DC
Catalog number	170E8883
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-6821BACC21
Generated	2026-08-05

Product Overview

Fuse-link, high speed, 200 A, DC 4000 V, size 2, 75 x 86 x 414 mm, aR, IEC, with indicator

FUSE 200A 4000V 2SKN/394 DC

Fuse, Fuse-link, high speed, 200 A, DC 4000 V, size 2, 75 x 86 x 414 mm, aR, IEC, with indicator, square body with offset bolted tags, indicator style K for microswitch, traction, Breaking Capacity 60 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Bussmann Series High speed fuses**

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed traction fuse Catalog Number 170E8883 EAN 5704057005500 UPC 051712689854 Product Length/Depth 416 mm Product Height 55 mm Product Width 77 mm Product Weight 136.8 g

Compliances EAC Certifications IEC Electrical data

Amperage Rating 200 A Voltage rating 4000 V Watt losses 228 W Breaking capacity 60 A Class Class aR Product specification

Fuse size 2

ETIM for 170E8883 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

2

Type of current (EF000143)

DC

Rated voltage DC (EF012281)

4000 V

Rated current (EF000227)

200 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

0.06 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

Top fuse status indicator

Power loss at rated current (EF012389)

228 W

Mounting holes (EF021553)

M8

Centre-to-centre distance of connections (EF021151)

393 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 200A 4000V 2SKN/394 DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.