

INDUSTRIAL COMPONENT DATA

High Speed Square Body 170L3697 EATON ELECTRIC

Fuse-link, high speed, 125 A, AC 1000 V, compact size 1, 43 x..

Brand: EATON - MOELLER | Manufacturer Part Number: High Speed - Square Body



Manufacturer	EATON - MOELLER
MPN / Reference	High Speed - Square Body
Catalog number	170L3697
Category	HRC fuse
Minimum order	3 Pcs
Document ID	EO-14F48623FB
Generated	2026-08-05

Product Overview

Fuse-link, high speed, 125 A, AC 1000 V, compact size 1, 43 x 58 x 135 mm, aR, IEC, single indicator

FUSE 125A 1000V 1*EK/110 AR

Fuse, Fuse-link, high speed, 125 A, AC 1000 V, compact size 1, 43 x 58 x 135 mm, aR, IEC, single indicator, square body with centre-bolted tags (slotted), french style, indicator style K for microswitch, Special type, semiconductor protection, IEC 60269-4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann fuses

Additional Product Information

Fuse-link, high speed, 125 A, AC 1000 V, compact size 1, 43 x 58 x 135 mm, aR, IEC, single indicator Fuse, Fuse-link, high speed, 125 A, AC 1000 V, compact size 1, 43 x 58 x 135 mm, aR, IEC, single indicator, square body with centre-bolted tags (slotted), french style, indicator style K for microswitch, Special type, semiconductor protection, IEC 60269-4 Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I] 125 A Rated voltage AC 1000 V Construction size compact size 1 Size 43 x 58 x 135 mm Utilization category aR Status indicator single indicator

Description french style

indicator style K for microswitch

Special type usable for size/applications semiconductor protection Standard/Approval IEC Shape square body with centre-bolted tags (slotted) Standards/Regulations IEC 60269-4 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (
[AFZ800015]) Construction size Other Rated current 125 A Rated voltage 1000 V Voltage type AC Rated switching capacity
kA Utilization category aR (accompanied semiconductor protection) Type of fuse status indicator Top fuse status indicator
Insulated metal gripping lugs (IMGL) No
ETIM for 170L3697 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse construction type according t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / High Speed - Square Body with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.