

## INDUSTRIAL COMPONENT DATA

# High Speed Square Body 170L7008 EATON ELECTRIC Fuse-link, high speed, 1250 A, AC 660 V, Size 3, 76 x 90 x 11..

Brand: EATON - MOELLER | Manufacturer Part Number: High Speed - Square Body



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | EATON - MOELLER          |
| MPN / Reference | High Speed - Square Body |
| Catalog number  | 170L7008                 |
| Category        | HRC fuse                 |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-DEBDD83C72            |
| Generated       | 2026-08-06               |

## Product Overview

Fuse-link, high speed, 1250 A, AC 660 V, Size 3, 76 x 90 x 111 mm, aR, DIN, IEC, single indicator

FUSE 1250A 660V 3TE/80 AR

Fuse, Fuse-link, high speed, 1250 A, AC 660 V, size 3, 76 x 90 x 111 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), indicator style T for microswitch, semiconductor protection, DIN 43653, IEC 60269-4, Breaking Capacity 200 kA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                  |
|--------------|----------------------------------|
| Catalog path | EATON - MOELLER > Bussmann fuses |
|--------------|----------------------------------|

## Additional Product Information

Fuse-link, high speed, 1250 A, AC 660 V, Size 3, 76 x 90 x 111 mm, aR, DIN, IEC, single indicator Fuse, Fuse-link, high speed, 1250 A, AC 660 V, size 3, 76 x 90 x 111 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), indicator style T for microswitch, semiconductor protection, DIN 43653, IEC 60269-4, Breaking Capacity 200 kA Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I] 1250 A Rated voltage AC 660 V Construction size size 3 Size 76 x 90 x 111 mm Utilization category aR Status indicator single indicator Description indicator style T for microswitch Breaking Capacity 200 kA usable for size/applications semiconductor protection Standard/Approval DIN

IEC Shape square body with centre-bolted tags (slotted) Standards/Regulations DIN 43653

IEC 60269-4 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ([email protected]  
[AFZ800015]) Construction size Other Rated current 1250 A Rated voltage 660 V Voltage type AC Rated switching capacity  
kA Utilization category aR (accompanied semiconductor protection) Type of fuse status indicator Top fuse status indicator  
Insulated metal gripping lugs (IMGL) No  
ETIM for 170L7008 Circuit breakers and fuses (EC004556)  
Feature Name  
Feature Value  
Fuse construction type acc...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / High Speed - Square Body with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.