

INDUSTRIAL COMPONENT DATA

High Speed Square Body 170L7092 EATON ELECTRIC

Fuse-link, high speed, 500 A, AC 660 V, Size 3, 76 x 76 x 63 ..

Brand: EATON - MOELLER | Manufacturer Part Number: High Speed - Square Body



Manufacturer	EATON - MOELLER
MPN / Reference	High Speed - Square Body
Catalog number	170L7092
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-70EB0805E8
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 500 A, AC 660 V, Size 3, 76 x 76 x 63 mm, aR, IEC, single indicator

FUSE 500A 660V 3DN/65 AR

Fuse, Fuse-link, high speed, 500 A, AC 660 V, size 3, 76 x 76 x 63 mm, aR, IEC, single indicator, square body with double-bolt flush end contacts, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 500 A, AC 660 V, Size 3, 76 x 76 x 63 mm, aR, IEC, single indicator Fuse, Fuse-link, high speed, 500 A, AC 660 V, size 3, 76 x 76 x 63 mm, aR, IEC, single indicator, square body with double-bolt flush end contacts, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I] 500 A Rated voltage AC 660 V Construction size size 3 Size 76 x 76 x 63 mm Utilization category aR Status indicator single indicator Breaking Capacity 200 kA usable for size/applications semiconductor protection Standard/Approval IEC Shape square body with double-bolt flush end contacts Standards/Regulations IEC 60269-4 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015]) Construction size Other Rated current 500 A Rated voltage 660 V Voltage type AC Rated switching capacity kA Utilization category aR (accompanied semiconductor protection) Type of fuse status indicator Top fuse status indicator Insulated metal gripping lugs (IMGL) No

ETIM for 170L7092 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

Other

Rated current (EF000227)

500 A

Utilization category according to IEC 60269 (EF0025...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / High Speed - Square Body with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.