

INDUSTRIAL COMPONENT DATA

High Speed Square Body 170L7292 EATON ELECTRIC

Fuse-link, high speed, 630 A, AC 1000 V, Size 3, 76 x 90 x 14..

Brand: EATON - MOELLER | Manufacturer Part Number: High Speed - Square Body



Manufacturer	EATON - MOELLER
MPN / Reference	High Speed - Square Body
Catalog number	170L7292
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-9E40A87864
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 630 A, AC 1000 V, Size 3, 76 x 90 x 141 mm, aR, IEC, single indicator

FUSE 630A 1000V 3STN/110 AR

Fuse, Fuse-link, high speed, 630 A, AC 1000 V, size 3, 76 x 90 x 141 mm, aR, IEC, single indicator, square body with centre-bolted tags (slotted), indicator style T for microswitch, Special type, semiconductor protection, IEC 60269-4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 630 A, AC 1000 V, Size 3, 76 x 90 x 141 mm, aR, IEC, single indicator Fuse, Fuse-link, high speed, 630 A, AC 1000 V, size 3, 76 x 90 x 141 mm, aR, IEC, single indicator, square body with centre-bolted tags (slotted), indicator style T for microswitch, Special type, semiconductor protection, IEC 60269-4 Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I] 630 A Rated voltage AC 1000 V Construction size size 3 Size 76 x 90 x 141 mm Utilization category aR Status indicator single indicator Description indicator style T for microswitch

Special type usable for size/applications semiconductor protection Standard/Approval IEC Shape square body with centre-bolted tags (slotted) Standards/Regulations IEC 60269-4 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015]) Construction size Other Rated current 630 A Rated voltage 1000 V Voltage type AC Rated switching capacity kA Utilization category aR (accompanied semiconductor protection) Type of fuse status indicator Top fuse status indicator

Insulated metal gripping lugs (IMGL) No
ETIM for 170L7292 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse construction type according to IEC 60269 (EF015865)
Other
Rated current (EF00022...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / High Speed - Square Body with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.