

INDUSTRIAL COMPONENT DATA

FUSE 400A 660V 2S/110 AR 170L8024 EATON ELECTRIC

Fuse-link, high speed, 400 A, AC 660 V, Size 2, 61 x 75 x 1..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 400A 660V 2S/110 AR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 400A 660V 2S/110 AR
Catalog number	170L8024
Category	HRC fuse
Minimum order	3 Pcs
Document ID	EO-C841F72453
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 400 A, AC 660 V, Size 2, 61 x 75 x 141 mm, aR, IEC, single indicator

FUSE 400A 660V 2S/110 AR

FUSE 400A 660V 2S/110 AR - Fuse-link, high speed, 400 A, AC 660 V, size 2, 61 x 75 x 141 mm, aR, IEC, single indicator, Special type

Fuse, Fuse-link, high speed, 400 A, AC 660 V, size 2, 61 x 75 x 141 mm, aR, IEC, single indicator, square body with centre-bolted tags (slotted), Special type, semiconductor protection, IEC 60269-4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series High speed fuses
--------------	---

Additional Product Information

Fuse-link, high speed, 400 A, AC 660 V, size 2, 61 x 75 x 141 mm, aR, IEC, single indicator, Special typeFuse, Fuse-link, high speed, 400 A, AC 660 V, size 2, 61 x 75 x 141 mm, aR, IEC, single indicator, square body with centre-bolted tags (slotted), Special type, semiconductor protection, IEC 60269-4Delivery program

Product rangeFuseBasic functionFuse-linkField of applicationhigh speedRated current [I]400 ARated voltageAC 660 VConstruction sizesize 2Size61 x 75 x 141 mmUtilization categoryaRStatus indicatorsingle indicatorDescriptionSpecial typeusable for size/applicationsemiconductor protectionStandard/ApprovalIECShapesquare body with centre-bolted tags (slotted)Standards/RegulationsIEC 60269-4Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015])Construction sizeOtherRated current400 ARated voltage660 VVoltage typeACRated switching

capacitykAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorTop fuse status indicatorInsulated metal gripping lugs (IMGL)No
ETIM for 170L8024 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
2
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
660 V
Rated current (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 400A 660V 2S/110 AR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.