

## INDUSTRIAL COMPONENT DATA

# FUSE 550A 1000V 2/110 AR 170L8031 EATON ELECTRIC

## Fuse-link, high speed, 550 A, AC 1000 V, Size 2, 61 x 61 x ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 550A 1000V 2/110 AR



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | EATON - MOELLER          |
| MPN / Reference | FUSE 550A 1000V 2/110 AR |
| Catalog number  | 170L8031                 |
| Category        | HRC fuse                 |
| Minimum order   | 3 Pcs                    |
| Document ID     | EO-3C52B253C6            |
| Generated       | 2026-08-06               |

### Product Overview

Fuse-link, high speed, 550 A, AC 1000 V, Size 2, 61 x 61 x 141 mm, aR, DIN, IEC, single indicator

FUSE 550A 1000V 2/110 AR

FUSE 550A 1000V 2/110 AR - Fuse-link, high speed, 550 A, AC 1000 V, size 2, 61 x 61 x 141 mm, aR, DIN, IEC, single indicator

Fuse, Fuse-link, high speed, 550 A, AC 1000 V, size 2, 61 x 61 x 141 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), semiconductor protection, DIN 43653, IEC 60269-4

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

### Additional Product Information

Fuse-link, high speed, 550 A, AC 1000 V, size 2, 61 x 61 x 141 mm, aR, DIN, IEC, single indicator  
Fuse, Fuse-link, high speed, 550 A, AC 1000 V, size 2, 61 x 61 x 141 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), semiconductor protection, DIN 43653, IEC 60269-4  
Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I]<sub>N</sub> 550 A Rated voltage AC 1000 V Construction size size 2 Size 61 x 61 x 141 mm Utilization category aR Status indicators single indicator usable for size/application semiconductor protection Standard/Approval DIN

IEC Shapes square body with centre-bolted tags (slotted) Standards/Regulations DIN 43653

IEC 60269-4 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ([email protected])

[AFZ800015])Construction sizeOtherRated current550 ARated voltage1000 VVoltage typeACRated switching capacity100 kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorTop fuse status indicatorInsulated metal gripping lugs (IMGL)No  
ETIM for 170L8031 Circuit breakers and fuses (EC004556)  
Feature Name  
Feature Value  
Fuse system according to IEC 60269 (EF017676)  
Other  
Fuse construction type according to IEC 60269 (EF015865)  
2  
Type of current (EF000143)  
AC  
Rated voltage AC (EF007682)  
1000 V  
Rated current (EF000227...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 550A 1000V 2/110 AR with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.