

INDUSTRIAL COMPONENT DATA

High Speed Square Body 170L8117 EATON ELECTRIC

Fuse-link, high speed, 375 A, AC 660 V, Size 2, 61 x 75 x 140..

Brand: EATON - MOELLER | Manufacturer Part Number: High Speed - Square Body



Manufacturer	EATON - MOELLER
MPN / Reference	High Speed - Square Body
Catalog number	170L8117
Category	HRC fuse
Minimum order	3 Pcs
Document ID	EO-271B3C8F64
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 375 A, AC 660 V, Size 2, 61 x 75 x 140 mm, aR, DIN, IEC, single indicator

FUSE 375A 660V 2TN/110 AR

FUSE 375A 660V 2TN/110 AR - Fuse-link, high speed, 375 A, AC 660 V, size 2, 61 x 75 x 140 mm, aR, DIN, IEC, type T indicator

Fuse, Fuse-link, high speed, 375 A, AC 660 V, size 2, 61 x 75 x 140 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), indicator style T for microswitch, semiconductor protection, DIN 43653, IEC 60269-4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

Fuse-link, high speed, 375 A, AC 660 V, size 2, 61 x 75 x 140 mm, aR, DIN, IEC, type T indicator
Fuse, Fuse-link, high speed, 375 A, AC 660 V, size 2, 61 x 75 x 140 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), indicator style T for microswitch, semiconductor protection, DIN 43653, IEC 60269-4
Delivery program
Product range
FuseBasic function
Fuse-linkField of application
high speedRated current [I]
375 ARated voltageAC 660 V
Construction size
size 2Size61 x 75 x 140 mmUtilization category
aRStatus indicator
type T indicatorusable for size/application
semiconductor protectionStandard/Approval
DIN

IECShapesquare body with centre-bolted tags (slotted)Standards/RegulationsDIN 43653

IEC 60269-4Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015])Construction sizeOtherRated current375 ARated voltage660 VVoltage typeACRated switching capacitykAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorTop fuse status indicatorInsulated metal gripping lugs (IMGL)No
ETIM for 170L8117 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse construction type according to IEC 60269 (EF015865)
Other
Rated current (EF000227)
375 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semicon...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / High Speed - Square Body with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.