

INDUSTRIAL COMPONENT DATA

High Speed Square Body 170L8931 EATON ELECTRIC

Fuse-link, high speed, 500 A, AC 1000 V, Size 2, 61 x 75 x 14..

Brand: EATON - MOELLER | Manufacturer Part Number: High Speed - Square Body



Manufacturer	EATON - MOELLER
MPN / Reference	High Speed - Square Body
Catalog number	170L8931
Category	HRC fuse
Minimum order	3 Pcs
Document ID	EO-5614C0795A
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 500 A, AC 1000 V, Size 2, 61 x 75 x 140 mm, aR, DIN, IEC, single indicator

FUSE 500A 1000V 2STN/110 AR

FUSE 500A 1000V 2STN/110 AR - Fuse-link, high speed, 500 A, AC 1000 V, size 2, 61 x 75 x 140 mm, aR, DIN, IEC, single indicator

Fuse, Fuse-link, high speed, 500 A, AC 1000 V, size 2, 61 x 75 x 140 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), indicator style T for microswitch, Special type, semiconductor protection, DIN 43653, IEC 60269-4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series High speed fuses
--------------	---

Additional Product Information

Fuse-link, high speed, 500 A, AC 1000 V, size 2, 61 x 75 x 140 mm, aR, DIN, IEC, single indicator
Fuse, Fuse-link, high speed, 500 A, AC 1000 V, size 2, 61 x 75 x 140 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), indicator style T for microswitch, Special type, semiconductor protection, DIN 43653, IEC 60269-4
Delivery program

Product range
Fuse
Basic function
Fuse-link
Field of application
high speed
Rated current [I]
500 A
Rated voltage
AC 1000 V
Construction size
size 2
Size
61 x 75 x 140 mm
Utilization category
aR
Status indicators
single indicator
usable for size/application
semiconductor protection
Standard/Approval
DIN

IEC
Shapes
square body with centre-bolted tags (slotted)
Standards/Regulations
DIN 43653

IEC 60269-4
Technical data
ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ( [AFZ800015]) Construction size Other Rated current 500 A Rated voltage 1000 V Voltage type AC Rated switching capacity kA Utilization category aR (accompanied semiconductor protection) Type of fuse status indicator Top fuse status indicator Insulated metal gripping lugs (IMGL) No

ETIM for 170L8931 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

Other

Rated current (EF000227)

500 A

Utilization category according to IEC 60269 (EF002572)

aR (a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / High Speed - Square Body with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.