

INDUSTRIAL COMPONENT DATA

FUSE 500A 2000V 3BKN/140 AR 170L9217 EATON ELECTRIC

Fuse-link, high speed, 500 A, AC 2000 V, Size 3, 74 x 90..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 500A 2000V 3BKN/140 AR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 500A 2000V 3BKN/140 AR
Catalog number	170L9217
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-601EE03BD1
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 500 A, AC 2000 V, Size 3, 74 x 90 x 143 mm, aR, IEC, single indicator

FUSE 500A 2000V 3BKN/140 AR

Fuse, Fuse-link, high speed, 500 A, AC 2000 V, size 3, 74 x 90 x 143 mm, aR, IEC, single indicator, square body with flush end contacts, indicator style K for microswitch, semiconductor protection, IEC 60269-4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170L9217 EAN 5996516008898

UPC 051712363068 Product Length/Depth 168 mm Product Height 76 mm Product Width 95 mm Product Weight 3133 g

Compliances Contact factory

RoHS Compliant Electrical data

Amperage Rating 500 A Voltage rating 2000 V Voltage type AC Watt losses 175 W Breaking capacity 100 kA Class Class

aR Product specification

Fuse size 3

ETIM for 170L9217 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

IEC 60269-4 flush end connections type A
Fuse construction type according to IEC 60269 (EF015865)
3
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
2000 V
Rated current (EF000227)
500 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Breaking capacity (EF005617)
100 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
Centre fuse status indicator
Power loss at rated current (EF012389)
175 W
Mounting holes (EF021553)
M12
Centre-to-centre distance of connections (EF021151)
143 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 500A 2000V 3BKN/140 AR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.