

INDUSTRIAL COMPONENT DATA

High Speed Square Body 170L9598 EATON ELECTRIC

Fuse-link, high speed, 725 A, AC 1000 V, Size 3, 76 x 76 x 75..

Brand: EATON - MOELLER | Manufacturer Part Number: High Speed - Square Body



Manufacturer	EATON - MOELLER
MPN / Reference	High Speed - Square Body
Catalog number	170L9598
Category	HRC fuse
Minimum order	2 Pcs
Document ID	EO-56D5E32A03
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 725 A, AC 1000 V, Size 3, 76 x 76 x 75 mm, aR, IEC, single indicator

FUSE 725A 1000V 3BN/75 AR

FUSE 725A 1000V 3BN/75 AR - Fuse-link, high speed, 725 A, AC 1000 V, size 3, 76 x 76 x 75 mm, aR, IEC, single indicator

Fuse, Fuse-link, high speed, 725 A, AC 1000 V, size 3, 76 x 76 x 75 mm, aR, IEC, single indicator, square body with flush end contacts, semiconductor protection, IEC 60269-4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

Fuse-link, high speed, 725 A, AC 1000 V, size 3, 76 x 76 x 75 mm, aR, IEC, single indicator
Fuse, Fuse-link, high speed, 725 A, AC 1000 V, size 3, 76 x 76 x 75 mm, aR, IEC, single indicator, square body with flush end contacts, semiconductor protection, IEC 60269-4
Delivery program

Product range
Fuse
Basic function
Fuse-link
Field of application
high speed
Rated current [I]
725 A
Rated voltage
AC 1000 V
Construction size
size 3
Size
76 x 76 x 75 mm
Utilization category
aR
Status indicators
single indicator
usable for
size/application
semiconductor protection
Standard/Approval
IEC
Shapes
square body with flush end contacts
Standards/Regulations
IEC 60269-4
Technical data
ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()
[AFZ800015])
Construction size
Other
Rated current
725 A
Rated voltage
1000 V
Voltage type
AC
Rated switching

capacitykAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorTop fuse status indicatorInsulated metal gripping lugs (IMGL)No
ETIM for 170L9598 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse construction type according to IEC 60269 (EF015865)
Other
Rated current (EF000227)
725 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Type of fuse status indicator (EF004473)
Top fuse status indicator

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / High Speed - Square Body with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.