

INDUSTRIAL COMPONENT DATA

FUSE 550A 750V DC 230FN/70 AR CU 170M1795 EATON

ELECTRIC Fuse-link, high speed, 550 A, DC 750 V, size 230, 2..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 550A 750V DC 230FN/70 AR CU



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 550A 750V DC 230FN/70 AR CU
Catalog number	170M1795
Category	HRC fuse
Minimum order	6 Pcs
Document ID	EO-837A8AC346
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 550 A, DC 750 V, size 230, 24 x 78 x 98 mm, aR, IEC, UL, visual indicator

FUSE 550A 690V 230FN/70 AR CU

FUSE 550A 750V DC 230FN/70 AR CU - Fuse-link, high speed, 550 A, AC 690 V, 50 kA, size 230, 24 x 78 x 98 mm, aR, IEC, UL, visual indicator

Fuse, Fuse-link, high speed, 550 A, AC 690 V, size 230, 24 x 78 x 98 mm, aR, IEC, UL, visual indicator, square body with offset bolted tags, IGBT circuits, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 550 A, AC 690 V, 50 kA, size 230, 24 x 78 x 98 mm, aR, IEC, UL, visual indicator Fuse, Fuse-link, high speed, 550 A, DC 750 V, size 230, 24 x 78 x 98 mm, aR, IEC, UL, visual indicator, square body with offset bolted tags, IGBT circuits, semiconductor protection, IEC 60269-4, Breaking Capacity 50 kA Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I]_N 550 A Rated voltage AC 690 V Construction size size 230 Size 24 x 78 x 98 mm Utilization category aR Status indicator visual indicator Breaking Capacity 50 kA Usable for size/applications IGBT circuits, semiconductor protection Standard/Approval IEC

UL Shapes square body with offset bolted tags Standards/Regulations IEC 60269-4 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015] Construction size Other Rated current 550 A Rated voltage 690 V Voltage type AC Rated switching capacity 50

kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorTop fuse status indicatorInsulated metal gripping lugs (IMGL)No
ETIM for 170M1795 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse construction type according to IEC 60269 (EF015865)
Other
Rated current (EF000227)
550 A
Utilization category according to IEC 60269 (EF002572)
aR (accompan...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 550A 750V DC 230FN/70 AR CU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.