

INDUSTRIAL COMPONENT DATA

FUSE 630A 750V DC 230FN/70 AR CU 170M1796 EATON

ELECTRIC Fuse-link, high speed, 630 A, DC 750 V, size 230, 2..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 630A 750V DC 230FN/70 AR CU

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 630A 750V DC 230FN/70 AR CU
Catalog number	170M1796
Category	HRC fuse
Minimum order	6 Pcs
Document ID	EO-7EC533D28C
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 630 A, DC 750 V, size 230, 24 x 78 x 98 mm, aR, IEC, UL, visual indicator

FUSE 630A 690V 230FN/70 AR CU

FUSE 630A 750V DC 230FN/70 AR CU - Fuse-link, high speed, 630 A, AC 690 V, 50 kA, size 230, 24 x 78 x 98 mm, aR, IEC, UL, visual indicator

Fuse, Fuse-link, high speed, 630 A, AC 690 V, size 230, 24 x 78 x 98 mm, aR, IEC, UL, visual indicator, square body with offset bolted tags, IGBT circuits, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

Fuse-link, high speed, 630 A, AC 690 V, 50 kA, size 230, 24 x 78 x 98 mm, aR, IEC, UL, visual indicator
Fuse, Fuse-link, high speed, 630 A, DC 750 V, size 230, 24 x 78 x 98 mm, aR, IEC, UL, visual indicator, square body with offset bolted tags, IGBT circuits, semiconductor protection, IEC 60269-4, Breaking Capacity 50 kA
Delivery program

Product range
FuseBasic function
Fuse-linkField of application
high speedRated current [I]
630 ARated voltageAC 690 V
Construction size
size 230Size
24 x 78 x 98 mmUtilization category
aRStatus indicator
visual indicatorBreaking Capacity
50 kAusable for size/applications
IGBT circuits, semiconductor protectionStandard/Approval
IEC

ULShapes
square body with offset bolted tagsStandards/Regulations
IEC 60269-4Technical data
ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()
[AFZ800015])Construction size
OtherRated current
630 ARated voltage
690 VVoltage type
ACRated switching capacity
50

kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorTop fuse status indicatorInsulated metal gripping lugs (IMGL)No
ETIM for 170M1796 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse construction type according to IEC 60269 (EF015865)
Other
Rated current (EF000227)
630 A
Utilization category according to IEC 60269 (EF002572)
aR (accompan...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 630A 750V DC 230FN/70 AR CU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.