

INDUSTRIAL COMPONENT DATA

FUSE 50A 690V 00BN/60 GR 170M2711 EATON ELECTRIC

Fuse-link, high speed, 50 A, AC 690 V, size 00, 30 x 48 x 6..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 50A 690V 00BN/60 GR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 50A 690V 00BN/60 GR
Catalog number	170M2711
Category	HRC fuse
Minimum order	5 Pcs
Document ID	EO-3CB7146D84
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 50 A, AC 690 V, size 00, 30 x 48 x 64 mm, aR, IEC, visual indicator

FUSE 50A 690V 00BN/60 GR

FUSE 50A 690V 00BN/60 GR - Fuse-link, high speed, 50 A, AC 690 V, 200 kA, size 00, 30 x 48 x 64 mm, aR, IEC, visual indicator

Fuse, Fuse-link, high speed, 50 A, AC 690 V, size 00, 30 x 48 x 64 mm, aR, IEC, visual indicator, square body with flush end contacts, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

Fuse-link, high speed, 50 A, AC 690 V, 200 kA, size 00, 30 x 48 x 64 mm, aR, IEC, visual indicator
Fuse, Fuse-link, high speed, 50 A, AC 690 V, size 00, 30 x 48 x 64 mm, aR, IEC, visual indicator, square body with flush end contacts, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA
Delivery program
Product range Fuse
Basic function Fuse-link
Field of application high speed
Rated current [I]_N 50 A
Rated voltage AC 690 V
Construction size size 00
Size 30 x 48 x 64 mm
Utilization category aR
Status indicator visual indicator
Breaking Capacity 200 kA
Usable for size/application semiconductor protection
Standard/Approval IEC
Shape square body with flush end contacts
Standards/Regulations IEC 60269-4
Technical data ETIM 7.0
Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()
[AFZ800015]
Construction size Other
Rated current 50 A
Rated voltage 690 V
Voltage type AC
Rated switching capacity 200

kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorTop fuse status indicatorInsulated metal gripping lugs (IMGL)No
ETIM for 170M2711 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse construction type according to IEC 60269 (EF015865)
Other
Rated current (EF000227)
50 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Type of fuse st...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 50A 690V 00BN/60 GR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.