

INDUSTRIAL COMPONENT DATA

FUSE 50A 690V 1*/80 AR UC 170M3009 EATON ELECTRIC

Fuse-link, high speed, 50 A, AC 690 V, compact DIN 1, 45 x..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 50A 690V 1*/80 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 50A 690V 1*/80 AR UC
Catalog number	170M3009
Category	HRC fuse
Minimum order	6 Pcs
Document ID	EO-AC4452C43E
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 50 A, AC 690 V, compact DIN 1, 45 x 45 x 104 mm, aR, DIN, IEC, single indicator

FUSE 50A 690V 1*/80 AR UC

FUSE 50A 690V 1*/80 AR UC - Fuse-link, high speed, 50 A, AC 690 V, 200 kA, compact DIN 1, 45 x 45 x 104 mm, aR, DIN, IEC, single indicator

Fuse, Fuse-link, high speed, 50 A, AC 690 V, compact DIN 1, 45 x 45 x 104 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), semiconductor protection, DIN 43653, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 50 A, AC 690 V, 200 kA, compact DIN 1, 45 x 45 x 104 mm, aR, DIN, IEC, single indicator
Fuse-link, high speed, 50 A, AC 690 V, compact DIN 1, 45 x 45 x 104 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), semiconductor protection, DIN 43653, IEC 60269-4, Breaking Capacity 200 kA
Delivery program
Product range FuseBasic function Fuse-linkField of application high speedRated current [I]_N 50 ARated voltage AC 690 VConstruction size compact DIN 1Size 45 x 45 x 104 mmUtilization category aRStatus indicators single indicatorBreaking Capacity 200 kAusable for size/application semiconductor protectionStandard/Approval DIN IEC 60269-4Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015])Construction sizeOtherRated current50 ARated voltage690 VVoltage typeACRated switching capacity200 kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorTop fuse status indicatorInsulated metal gripping lugs (IMGL)No
ETIM for 170M3009 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
Other
Type of curren...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 50A 690V 1*/80 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.