

INDUSTRIAL COMPONENT DATA

FUSE 315A 690V 1FKE/115 AR UC 170M4760 EATON

ELECTRIC Fuse-link, high speed, 315 A, AC 690 V, size 1, 53 x 6..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 315A 690V 1FKE/115 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 315A 690V 1FKE/115 AR UC
Catalog number	170M4760
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-107E2051D3
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 315 A, AC 690 V, size 1, 53 x 69 x 136 mm, aR, IEC, UL, single indicator

FUSE 315A 690V 1FKE/115 AR UC

Fuse-link, high speed, 315 A, AC 690 V, size 1, 53 x 69 x 136 mm, aR, IEC, UL, single indicator, 115 mm fixing centres

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series High speed fuses
--------------	---

Additional Product Information

General specifications

Product Name Eaton Busmann series high speed square body fuse Catalog Number 170M4760 EAN 5996516013984

UPC 051712259804 Product Length/Depth 73 mm Product Height 52 mm Product Width 170 mm Product Weight 562 g

Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated Electrical data

Amperage Rating 315 A Voltage rating 690 V Voltage type AC Clearing (I2T) 42000 at 660 V Pre arc (I2T) 6200 Watt losses

58 W Breaking capacity 200 kA Class Class aR Product specification

Fuse size 1 Fitted with: Type K Indicator for micro

ETIM for 170M4760 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

1

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

690 V

Rated current (EF000227)

315 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

Top fuse status indicator

Power loss at rated current (EF012389)

58 W

Mounting holes (EF021553)

M12

Centre-to-centre distance of connections (EF021151)

115 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 315A 690V 1FKE/115 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.