

INDUSTRIAL COMPONENT DATA

FUSE 200A 1000V 1BKN/75 AR 170M4952 EATON ELECTRIC

Fuse-link, high speed, 200 A, AC 1000 V, size 1, 52 x 69 ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 200A 1000V 1BKN/75 AR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 200A 1000V 1BKN/75 AR
Catalog number	170M4952
Category	HRC fuse
Minimum order	2 Pcs
Document ID	EO-2F67BE150A
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 200 A, AC 1000 V, size 1, 52 x 69 x 74 mm, aR, IEC, UL, single indicator

FUSE 200A 1000V 1BKN/75 AR

FUSE 200A 1000V 1BKN/75 AR - Fuse-link, high speed, 200 A, AC 1000 V, 125 kA, size 1, 52 x 69 x 74 mm, aR, IEC, UL, type K indicator

Fuse-link, high speed, 200 A, AC 1000 V, size 1, 52 x 69 x 74 mm, aR, IEC, UL, type K indicator, flush end, M8

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 200 A, AC 1000 V, 125 kA, size 1, 52 x 69 x 74 mm, aR, IEC, UL, type K indicator Fuse, Fuse-link, high speed, 200 A, AC 1000 V, size 1, 52 x 69 x 74 mm, aR, IEC, UL, single indicator, square body with flush end contacts, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 125 kA Delivery program Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I] 200 A Rated voltage AC 1000 V Construction size size 1 Size 52 x 69 x 74 mm Utilization category aR Status indicator type K indicator Breaking Capacity 125 kA Usable for size/application semiconductor protection Standard/Approval IEC UL Shapes square body with flush end contacts Standards/Regulations IEC 60269-4 Technical data ETIM 7.0 Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015]) Construction size Other Rated current 200 A Rated voltage 1000 V Voltage type AC Rated switching capacity 125 kA Utilization category aR (accompanied semiconductor protection) Type of fuse status indicator Other Insulated metal

gripping lugs (IMGL)No

ETIM for 170M4952 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

1

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

1000....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 200A 1000V 1BKN/75 AR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.