

INDUSTRIAL COMPONENT DATA

FUSE 315A 1250V 2BKN/80 AR CU 170M5440 EATON

ELECTRIC FUSE 315A 1250V 2BKN/80 AR CU

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 315A 1250V 2BKN/80 AR CU



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 315A 1250V 2BKN/80 AR CU
Catalog number	170M5440
Category	HRC fuse
Minimum order	2 Pcs
Document ID	EO-906ABBDA6C
Generated	2026-08-06

Product Overview

FUSE 315A 1250V 2BKN/80 AR CU

Fuse-link, high speed, 315 A, AC 1250 V, size 2, 61 x 77 x 81 mm, aR, UL, IEC, single indicator

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 315 A, AC 1250 V, size 2, 61 x 77 x 81 mm, aR, UL, IEC, single indicator

Fuse, Fuse-link, high speed, 315 A, AC 1250 V, size 2, 61 x 77 x 81 mm, aR, IEC, UL, single indicator, square body with flush end contacts, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 100 kA

Delivery program

Product range

Fuse

Basic function

Fuse-link

Field of application

high speed

Rated current [I]_N 315 A

Rated voltage AC 1250 V

Construction size

size 2

Size 61 x 77 x 81 mm

Utilization category

aR

Status indicator

single indicator

usable for size/application

semiconductor protection

Standard/Approval

UL

IEC

Shapes

square body with special bladed contacts

Standards/Regulations

UL Recognized

IEC Rated

Technical data

ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) ( [BAB264011])

Fuse construction type according to IEC 60269

2

Type of current

AC

Rated voltage AC 1250 V

Rated voltage DC

V

Rated current

315 A

Utilization category

aR (accompanied semiconductor protection)

Breaking capacity

100 kA

Colour

code

None

Type of fuse status indicator

Top fuse status indicator

Power loss at rated current

75 W

Mounting holes

M10

Centre-to-centre distance of connections

80.3 mm

ETIM for 170M5440 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fus...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 315A 1250V 2BKN/80 AR CU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.