

## INDUSTRIAL COMPONENT DATA

# High Speed Square Body 170M5562 EATON ELECTRIC Fuse-link, high speed, 630 A, AC 690 V, size 2, 61 x 77 x 51 ..

Brand: EATON - MOELLER | Manufacturer Part Number: High Speed - Square Body



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | EATON - MOELLER          |
| MPN / Reference | High Speed - Square Body |
| Catalog number  | 170M5562                 |
| Category        | HRC fuse                 |
| Minimum order   | 6 Pcs                    |
| Document ID     | EO-53FD6AA1D0            |
| Generated       | 2026-08-06               |

## Product Overview

Fuse-link, high speed, 630 A, AC 690 V, size 2, 61 x 77 x 51 mm, aR, IEC, UL, type K indicator, flush end, 16 UNC

FUSE 630A 690V 2GKN/50 AR UC

FUSE 630A 690V 2GKN/50 AR UC - Fuse-link, high speed, 630 A, AC 690 V, size 2, 61 x 77 x 51 mm, aR, UL, IEC, 16 UNC, square body with flush end contacts

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                 |
|--------------|-----------------|
| Catalog path | EATON - MOELLER |
|--------------|-----------------|

## Additional Product Information

Fuse-link, high speed, 630 A, AC 690 V, size 2, 61 x 77 x 51 mm, aR, UL, IEC, 16 UNC, square body with flush end contacts  
Fuse, Fuse-link, high speed, 630 A, AC 690 V, size 2, 61 x 77 x 51 mm, aR, IEC, UL, single indicator, square body with flush end contacts, indicator style K for microswitch, US thread, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA  
Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I]<sub>n</sub> 630 A Rated voltage AC 690 V Construction size size 2 Size 61 x 77 x 51 mm Utilization category aR Status indicator type K indicator Description 16 UNC usable for size/application semiconductor protection Standard/Approval UL

IEC Shapes square body with flush end contacts Standards/Regulations IEC Rated

UL Recognized Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) ([email protected])

[BAB264011]) Fuse construction type according to IEC 60269 Other Type of current Rated voltage AC 690 V Rated voltage

DCVRated current630 AUtilization categoryaR (accompanied semiconductor protection)Breaking capacitykAColour codeType of fuse status indicatorOtherPower loss at rated current90 WMounting holesCentre-to-centre distance of connectionsmm

ETIM for 170M5562 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF01767...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / High Speed - Square Body with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.