

INDUSTRIAL COMPONENT DATA

FUSE 315A 1250V 2FKE/115 AR CU 170M5740 EATON

ELECTRIC Fuse-link, high speed, 800 A, AC 2000 V, size 3, 99 X..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 315A 1250V 2FKE/115 AR CU



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 315A 1250V 2FKE/115 AR CU
Catalog number	170M5740
Category	HRC fuse
Minimum order	3 Pcs
Document ID	EO-9F4FE7C776
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 800 A, AC 2000 V, size 3, 99 x 171 x 142 mm, aR, IEC, single indicator, dual body

FUSE 315A 1250V 2FKE/115 AR CU

Fuse-link, high speed, 315 A, AC 1250 V, size 2, 61 x 77 x 160 mm, aR, IEC, UL, single indicator

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Busmann series high speed square body fuse Catalog Number 170M5740 EAN 5027590458382

UPC 051712262309 Product Length/Depth 161 mm Product Height 59 mm Product Width 76 mm Product Weight 773 g

Compliances CE

RoHS Compliant

EAC Certifications IEC

UL Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 315 A

Breaking capacity 100 kA Fuse indicator Top fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization

category aR (accompanied semiconductor protection) Voltage type AC Fuse size 2 Rated voltage AC 1250 V

Center-to-center distance of connections 114 mm Current type AC Mounting dimension M12 Class Class aR Watt losses 75

W Fuse shape Square body, center bolted tags Pre arc (I2T) 13000 Color None Interrupt rating 100 kAIC Fitted with: Type K Indicator for micro Construction size 2 Packaging type Standard Voltage rating 1250 V Fuse type US Style

FKE/115 Type K indicator for micro Fuse system (according to IEC 60269) Other

ETIM for 170M5740 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

2

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

1250 V

Rated current (EF000227)

315 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

100 kA

Colour...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 315A 1250V 2FKE/115 AR CU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.