

INDUSTRIAL COMPONENT DATA

FUSE 1100A 690V 3FU/115 AR UC 170M6715 EATON

ELECTRIC Fuse-link, high speed, 1100 A, AC 690 V, size 3, 67 X ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 1100A 690V 3FU/115 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 1100A 690V 3FU/115 AR UC
Catalog number	170M6715
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-20EC87A615
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 1100 A, AC 690 V, size 3, 67 x 92 x 155 mm, aR, IEC, UL

FUSE 1100A 690V 3FU/115 AR UC

FUSE 1100A 690V 3FU/115 AR UC - Fuse-link, high speed, 1100 A, AC 690 V, 200 kA, size 3, 67 x 92 x 155 mm, aR, IEC, UL, US style

Fuse, Fuse-link, high speed, 1100 A, AC 690 V, size 3, 67 x 92 x 155 mm, aR, IEC, UL, square body with centre-bolted tags, US style, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 1100 A, AC 690 V, 200 kA, size 3, 67 x 92 x 155 mm, aR, IEC, UL, US style
Fuse, Fuse-link, high speed, 1100 A, AC 690 V, size 3, 67 x 92 x 155 mm, aR, IEC, UL, square body with centre-bolted tags, US style, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application high speed
Rated current [I]
1100 A
Rated voltage AC 690 V
Construction size size 3
Size 67 x 92 x 155 mm
Utilization category aR
Description US style
Breaking Capacity 200 kA
Usable for size/applications semiconductor protection
Standard/Approval IEC

UL
Shapes square body with centre-bolted tags
Standards/Regulations IEC 60269-4
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (
[AFZ800015])Construction sizeOtherRated current1100 ARated voltage690 VVoltage typeACRated switching capacity200
kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorNoneInsulated metal gripping
lugs (IMGL)No

ETIM for 170M6715 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

Other

Rated current (EF000227)

1100 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Type of fuse status indicator (EF004473)

None

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 1100A 690V 3FU/115 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.