

INDUSTRIAL COMPONENT DATA

HLR40/1(DC)600V/S 360042 Y7-360042 EATON ELECTRIC

HLR40/1(DC)600V/S

Brand: EATON - MOELLER | Manufacturer Part Number: HLR40/1(DC)600V/S



Manufacturer	EATON - MOELLER
MPN / Reference	HLR40/1(DC)600V/S
Catalog number	Y7-360042
Category	Solid state relay
Minimum order	1 Pcs
Document ID	EO-F886444E4B
Generated	2026-08-01

Product Overview

HLR40/1(DC)600V/S

Eaton Moeller series HLR Solid-state relay, 1-phase, 43 A, 600 - 600 V, DC, high fuse protection

Solid-state relay, 1-phase, 43 A, 600 - 600 V, DC, high fuse protection, IP20, Screw connection, Switching at zero-crossing, CE, UL 508, EAC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Standard Soft Starters

Additional Product Information

General specifications

Product Name Eaton Moeller series HLR solid state relay Catalog Number 360042 Model Code HLR40/1(DC)600V/S EAN 4015081998104 Product Length/Depth 141 mm Product Height 110 mm Product Width 35.6 mm Product Weight 0.42 kg

Compliances CE Marked

RoHS Compliant Certifications CE

UL 508

EAC

UL-File No.: E251034, UL report applies to both US and Canada Features & Functions

Features Modular version Functions Switching at zero-crossing Electrical connection type for auxiliary- and control-current circuit Screw connection Electrical connection type of main circuit Screw connection General

Degree of protection IP20 Frequency rating 45 Hz - 65 Hz Mounting position Mount device in specified orientation and do not obstruct the heatsink Number of phases 1 Number of pilot lights 1 Overvoltage category III Pollution degree 2 Rated

impulse withstand voltage (Uimp) 6 kV (1.2/50 us) Series HLR Shock resistance 15/11 g/ms (according to EN 50155, EN 61373) Type Solid-state relay Vibration resistance 2 g/axis (2-100 Hz, IEC 60068-2-6, EN 50155, EN 61373) Voltage type DC Climatic environmental conditions
Altitude 9 Ambient storage temperature - min -40 °C Ambient storage temperature - max 100 °C Climatic proofing 95% relative humidity non-condensing at 40°C Operating temperature - min -40 °C Operating temperature - max 80 °C Electro magnetic compatibility
Air discharge 8 kV (according to IEC/EN 61000-4-2) Burst Impulse Main: 2 kV, 5 kHz PC 1 (according to IEC/EN 61000-4-4) Co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / HLR40/1(DC)600V/S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.