

INDUSTRIAL COMPONENT DATA

HN-C10/1N 194849 Y7-194849 EATON ELECTRIC Miniature Circuit breaker 1N-pole C-char 10-A

Brand: EATON - MOELLER | Manufacturer Part Number: HN-C10/1N



Manufacturer	EATON - MOELLER
MPN / Reference	HN-C10/1N
Catalog number	Y7-194849
Category	Miniature circuit breaker (MCB)
Minimum order	1 unit
Document ID	EO-64B9B7F806
Generated	2026-08-06

Product Overview

Miniature Circuit breaker 1N-pole C-char 10-A

HN-C10/1N

Eaton Moeller series xPole Home - HN/HN-HX MCB. HN, xPole Home, 1-pole+N, tripping characteristic: C, rated current In: 10 A, rated switching capacity IEC/EN 60898-1: 6 kA

Miniature circuit breaker (MCB), HN, xPole Home, 1-pole+N, tripping characteristic: C, rated current In: 10 A, rated switching capacity according to IEC/EN 60898-1: 6 kA, Switchgear for residential and commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Built-in depth (EF000218)	44 mm
Release characteristic (EF000889)	C
Number of poles (total) (EF008618)	2
Number of protected poles (EF005548)	1
Rated current (EF000227)	10 A
Rated voltage (EF000228)	230 V
Rated insulation voltage Ui (EF001366)	440 V
Rated impulse withstand voltage Uimp (EF011980)	4 kV
Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V (EF009556)	6 kA
Voltage type (EF000187)	AC
Rated short-circuit breaking capacity Icn according to EN 60898 at 400 V (EF009555)	6 kA
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V (EF009557)	0 kA

CONTINUED

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V (EF009558)	0 kA
Frequency (EF000416)	50 Hz
Power loss (EF005387)	1.6 W
Current limiting class (EF002568)	3
Flush-mounted installation (EF007517)	Yes
Concurrently switching neutral conductor (EF005997)	Yes
Over voltage category (EF002569)	3
Pollution degree (EF002570)	3
Additional equipment possible (EF008148)	Yes
Width in number of modular spacings (EF002950)	2
Degree of protection (IP) (EF005474)	IP20
Ambient temperature during operating (EF007515)	-25 °C
Connectable conductor cross section multi-wired (EF007343)	1 mm ²
Connectable conductor cross section solid-core (EF007337)	1 mm ²
Explosion-proof (EF004663)	No

Classification & Catalog Path

Catalog path	EATON - MOELLER > Home Switchgear
--------------	-----------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller series xPole Home - HN/HN-HX MCB

Catalog Number 194849

Model Code HN-C10/1N

EAN 9010238063334

Product Length/Depth 85 mm

Product Height 73 mm

Product Width 35.4 mm

Product Weight 0.216 kg

Compliances RoHS conform

Delivery program

Application Switchgear for residential and commercial applications

xPole Home - Switchgear for residential applications

Number of poles Single-pole + N

Number of poles (total) 2

Number of poles (protected) 1

Tripping characteristic C

Release characteristic C
Amperage Rating 10 A
Type HN
Miniature circuit breaker
Technical Data - Electrical
Voltage type AC
Rated operational voltage (Ue) - max 230 V
Rated insulation voltage (Ui) 440 V
Rated impulse withstand voltage (Uimp) 4 kV
Frequency rating - min 50 Hz
Frequency rating - max 60 Hz
Rated switching capacity (IEC/EN 60898-1) 6 kA
Overvoltage category III
Pollution degree 3
Technical Data - Mechanical
Width in number of modular spacings 2
Built-in depth 44 mm
Degree of protection IP20
Connectable conductor cross section (solid-core) - min 1 mm²
Connectable con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / HN-C10/1N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.