

INDUSTRIAL COMPONENT DATA

+IP23/02 200623 Y7-200623 EATON ELECTRIC Housing, IP23 x, HxWxD 192x184x160mm, for transformer. Can only be ..

Brand: EATON - MOELLER | Manufacturer Part Number: +IP23/02



Manufacturer	EATON - MOELLER
MPN / Reference	+IP23/02
Catalog number	Y7-200623
Category	Empty enclosure for switchgear
Minimum order	1 Pcs
Document ID	EO-CC9CBD53F4
Generated	2026-08-06

Product Overview

Housing, IP23_x, HxWxD=192x184x160mm, for transformer. Can only be sold assembled.

+IP23/02

IP23 enclosures, For use with STZ0.2 ... STZ0.5

IP23 enclosure for STZ0.2 to STZ0.5, enclosure can be used with primary or secondary voltage > 110 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Transformers
--------------	--------------------------------

Additional Product Information

IP23 enclosures, For use with STZ0.2 ... STZ0.5IP23 enclosure for STZ0.2 to STZ0.5, enclosure can be used with primary or secondary voltage > 110 V

General specificationsProduct nameEaton Moeller® series Accessory HousingPart

no.+IP23/02EAN4015082006235Product Length/Depth192 millimetreProduct height184 millimetreProduct width160

millimetreProduct weight1.9 kilogramCertificationsUL ListedProduct TradenameNoneProduct TypeAccessoryProduct Sub

TypeHousingCatalog NotesElectrical characteristics: all details for no-load loss, short-circuit loss (copper losses),

short-circuit voltage and efficiency values relate to a temperature of 20 °CFeatures & FunctionsEnclosure

materialSteelFeaturesSeparate windingsGeneral informationAmbient operating temperature - min-25 °CAmbient operating

temperature - max40 °CDegree of protectionIP23

NEMA OtherDuty factor100 %Insulation classF

BModelBuilt-inProduct categoryAccessoriesDesign verificationEquipment heat dissipation, current-dependent Pvid0 WHeat

dissipation capacity Pdis39 WHeat dissipation per pole, current-dependent Pvid0 WRated operational current for specified

heat dissipation (In)0 AStatic heat dissipation, non-current-dependent Pvs0 WRadiated heat dissipation with separate mounting39 W (at an ambient temperature of 20 °C)10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2.3.2 Verification of resistance of insulating ma...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IP23/02 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.