

## INDUSTRIAL COMPONENT DATA

**+IP23/31 200753 Y7-200753 EATON ELECTRIC Housing, IP23 x, HxWxD 231x254x203mm, for transformer. Can only be ..**

Brand: EATON - MOELLER | Manufacturer Part Number: +IP23/31



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | EATON - MOELLER                |
| MPN / Reference | +IP23/31                       |
| Catalog number  | Y7-200753                      |
| Category        | Empty enclosure for switchgear |
| Minimum order   | 1 Pcs                          |
| Document ID     | EO-91D0997936                  |
| Generated       | 2026-08-06                     |

## Product Overview

Housing, IP23\_x, HxWxD=231x254x203mm, for transformer. Can only be sold assembled.

+IP23/31

IP23 enclosures, For use with DTZ0.25 ... DTZ0.63

IP23 enclosure for DTZ0.25 to DTZ0.63, enclosure can be used with primary or secondary voltage of 42 V to max, 1000 V including tapping

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Transformers

## Additional Product Information

IP23 enclosures, For use with DTZ0.25 ... DTZ0.63IP23 enclosure for DTZ0.25 to DTZ0.63, enclosure can be used with primary or secondary voltage of 42 V to max, 1000 V including tapping

General specificationsProduct nameEaton Moeller® series Accessory HousingPart

no.+IP23/31EAN4015082007539Product Length/Depth231 millimetreProduct height254 millimetreProduct width203

millimetreProduct weight6.9 kilogramCompliancesCEProduct TradenameNoneProduct TypeAccessoryProduct Sub

TypeHousingCatalog NotesElectrical characteristics: all details for no-load loss, short-circuit loss (copper losses),

short-circuit voltage and efficiency values relate to a temperature of 20 °CFeatures & FunctionsEnclosure

materialSteelFeaturesSeparate windingsGeneral informationAmbient operating temperature - min-25 °CAmbient operating temperature - max40 °CDegree of protectionIP23

NEMA OtherDuty factor100 %Insulation classF

BModelBuilt-inProduct categoryAccessoriesDesign verificationEquipment heat dissipation, current-dependent Pvid0 WHeat

dissipation capacity  $P_{diss}$  75 W Heat dissipation per pole, current-dependent  $P_{vid}$  0 W Rated operational current for specified heat dissipation ( $I_n$ ) 0 A Static heat dissipation, non-current-dependent  $P_{vs}$  0 W Radiated heat dissipation with separate mounting 75 W (at an ambient temperature of 20 °C) 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IP23/31 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.